

Title (en)

Method for automatic doffing operation and doffing apparatus

Title (de)

Verfahren und Vorrichtung zum automatischen Spulenwechsel

Title (fr)

Procédé et dispositif pour le changement automatique de bobines

Publication

**EP 1693492 A2 20060823 (EN)**

Application

**EP 06000955 A 20060117**

Priority

JP 2005039766 A 20050216

Abstract (en)

The present invention relates to an automatic doffing operation. Conventionally if in spite of a failure in a yarn drawing-out operation, a yarn hooking operation is performed and an empty bobbin is uselessly supplied, an operator is thus forced to remove the bobbin. The present invention includes a full-package taking-out operation step of taking a bobbin (17) with a package (6) out of a cradle, a yarn drawing-out operation step of using a yarn drawing-out device (20) to start drawing out a spun yarn and then catching the spun yarn, and a yarn hooking operation step of supplying an empty bobbin (17) to the cradle and hooking the spun yarn on the bobbin (17) to return a doffing operation to an initial state. If the yarn fails to be caught during the yarn drawing-out operation step, a reverse returning step is executed instead of the yarn hooking operation step to reversely rotate a motor to return the doffing operation to its initial state without executing the yarn hooking operation step.

IPC 8 full level

**D01H 9/10** (2006.01)

CPC (source: EP)

**D01H 9/10** (2013.01)

Designated contracting state (EPC)

CH DE LI

DOCDB simple family (publication)

**EP 1693492 A2 20060823; EP 1693492 A3 20080206; CN 100545332 C 20090930; CN 1821462 A 20060823; JP 2006225092 A 20060831**

DOCDB simple family (application)

**EP 06000955 A 20060117; CN 200610008519 A 20060216; JP 2005039766 A 20050216**