

Title (en)

BLOCKING DEVICE IN THE EVENT OF SAWING OF A PLUG, PARTICULARLY FOR A SECURITY LOCK

Title (de)

EINRICHTUNG ZUM SPERREN DES SCHLIESSZYLINDERS IM FALLE DESSEN ZERSÄGUNG, INSBESONDERE FÜR EIN SICHERHEITSSCHLOSS

Title (fr)

DISPOSITIF DE BLOCAGE ET DE DEBLOCAGE D'UN MOUVEMENT D'ACTIONNEMENT, NOTAMMENT POUR SERRURE DE SURETE, MUNI DE MOYENS DE BLOCAGE EN CAS DE TRONCONNEMENT DU BARILLET

Publication

EP 1697606 B1 20100630 (FR)

Application

EP 04742437 A 20040405

Priority

- FR 2004000844 W 20040405
- FR 0314201 A 20031203

Abstract (en)

[origin: FR2863295A1] The device has a mechanism (10) with a cylinder (50) in which a keying pattern authentication device and a pumping arrangement (40) are housed. The authentication device adopts, in a stop position of a key, either an authorization configuration in which the key can actuate the arrangement, or an interdiction configuration in which the key is locked. Movable locking units (71) lock the arrangement when the cylinder is cut.

IPC 8 full level

E05B 17/20 (2006.01); **E05B 29/00** (2006.01)

CPC (source: EP)

E05B 17/2092 (2013.01); **E05B 29/0033** (2013.01)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

FR 2863295 A1 20050610; FR 2863295 B1 20060310; AT E472651 T1 20100715; DE 602004027944 D1 20100812; EP 1697606 A1 20060906; EP 1697606 B1 20100630; ES 2347960 T3 20101126; PT 1697606 E 20100929; WO 2005066439 A1 20050721

DOCDB simple family (application)

FR 0314201 A 20031203; AT 04742437 T 20040405; DE 602004027944 T 20040405; EP 04742437 A 20040405; ES 04742437 T 20040405; FR 2004000844 W 20040405; PT 04742437 T 20040405