

Title (en)
PNEUMATIC TIRE

Title (de)
LUFTREIFEN

Title (fr)
PNEUMATIQUE

Publication
EP 1698493 A1 20060906 (EN)

Application
EP 04819864 A 20041201

Priority
• JP 2004017873 W 20041201
• JP 2003403579 A 20031202

Abstract (en)
There is provided a side-reinforced run flat tire capable of enhancing safety at the time of running with its internal pressure kept in a range of 50 to 150 kPa. A belt-reinforcing layer 8a is made up of a composite cord formed by twisting a high-modulus fiber and a low-modulus fiber together. A stress-strain curve of the composite cord preferably has an inflection point between a low-modulus region, and a high-modulus region, set to fall in a range of 2 to 7 % in strain. In a region of the composite cord, smaller in strain, deformation of a tread is more tolerated than in the case of using a low-modulus cord, and deflection of the sidewall is more deterred than in the case of using the high-modulus cord. Further, when the strain of the composite cord reaches the high-modulus region, the composite cord exhibits modulus of elasticity higher than that in the case of using the low-modulus cord, so that the tread does not undergo excessive deformation such as will occur in the case of using the low-modulus cord. As a result, there will occur enhancement in center ground-contact length as well as durability of the tire when an internal pressure thereof is kept in the range of 50 to 100 kPa, resulting in enhancement in safety at the time of running with the internal pressure kept in the range of 50 to 100 kPa.

IPC 8 full level
B60C 17/00 (2006.01); **B60C 9/20** (2006.01); **B60C 9/22** (2006.01)

CPC (source: EP US)
B60C 9/005 (2013.01 - EP US); **B60C 9/22** (2013.01 - EP US); **B60C 17/0009** (2013.01 - EP US)

Cited by
EP2017093A3; US8104525B2; US8622105B2; US11046113B2; WO2017111902A1; WO2017112630A1

Designated contracting state (EPC)
DE ES FR GB IT

DOCDB simple family (publication)
EP 1698493 A1 20060906; **EP 1698493 A4 20070502**; **EP 1698493 B1 20100811**; CN 1882443 A 20061220; DE 602004028653 D1 20100923; JP 2005161998 A 20050623; US 2007095450 A1 20070503; WO 2005053971 A1 20050616

DOCDB simple family (application)
EP 04819864 A 20041201; CN 200480034114 A 20041201; DE 602004028653 T 20041201; JP 2003403579 A 20031202; JP 2004017873 W 20041201; US 58151804 A 20041201