

Title (en)
Detent escapement for timepieces

Title (de)
Chronometerhemmung für Uhren

Title (fr)
Echappement à détente pour pièce d'horlogerie

Publication
EP 1708047 B1 20080326 (FR)

Application
EP 05006851 A 20050330

Priority
EP 05006851 A 20050330

Abstract (en)
[origin: EP1708047A1] The escapement has rotating plates (1) with a large plate (4) carrying a pulse pallet (5) surmounted on an actuating finger (14), and a small plate (23) with a notch (22). A blocker (6) carries blocking units (80) to block an escape wheel (2), and an actuating finger (11) arranged to cooperate with the finger (14). The blocker has a feeler (20) terminated by a nose (21). The nose acts at the small plate and with the notch. The fingers (14, 11) are fixed rigidly, respectively, on the large plate and the blocker.

IPC 8 full level
G04B 15/06 (2006.01)

CPC (source: EP US)
G04B 15/06 (2013.01 - EP US)

Cited by
RU2629546C2; EP3121660A1; EP3907566A1; CN113608424A; US7553068B2; US7607822B2; US7708455B2; US7604395B2; EP2450757A1; US8556499B2; EP2450756A1; US8602637B2; US11906929B2; EP2450755A1; US8439556B2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1708047 A1 20061004; EP 1708047 B1 20080326; AT E390653 T1 20080415; CN 100547503 C 20091007; CN 1841241 A 20061004;
DE 602005005633 D1 20080508; DE 602005005633 T2 20090416; HK 1091558 A1 20070119; JP 2006284580 A 20061019;
JP 4896559 B2 20120314; SG 126106 A1 20061030; US 2006221774 A1 20061005; US 7494268 B2 20090224

DOCDB simple family (application)
EP 05006851 A 20050330; AT 05006851 T 20050330; CN 200610065990 A 20060329; DE 602005005633 T 20050330;
HK 06112122 A 20061103; JP 2006093882 A 20060330; SG 200601993 A 20060324; US 27765206 A 20060328