

Title (en)

ONE-SIDED DOUBLE FOLDING FRAME FOR ROLLER PRESSES

Title (de)

EINSEITIG DOPPELT AUFKLAPPBARER RAHMEN FÜR WALZENPRESSE

Title (fr)

CADRE DE PRESSE A ROULEAUX DOUBLEMENT RELEVABLE SUR UN COTE

Publication

**EP 1708815 A1 20061011 (DE)**

Application

**EP 05700698 A 20050105**

Priority

- EP 2005000035 W 20050105
- DE 202004001187 U 20040127

Abstract (en)

[origin: US2007187538A1] A roller press with a hinged frame having a frame substructure, a frame top wall and two head pieces arranged at the side, with at least one head piece, with a part of the frame top wall arranged on it, forming a side flap which is arranged on the frame substructure for opening out. In the hinged frame at least two rollers are placed, positioned adjacently, which, in a roller removal position of the hinged frame, can be removed from the hinged frame sideways via the removal opening formed by the opened-out side flap. The part of the frame top wall assigned to the side flap is arranged for swivelling relative to the head piece by means of an articulated joint arranged on the associated head piece, whereby the swivel axis of the articulated joint is arranged essentially parallel to the axes of the rollers

IPC 8 full level

**B02C 4/28** (2006.01); **B02C 4/02** (2006.01); **B30B 3/04** (2006.01); **B30B 15/04** (2006.01)

CPC (source: EP US)

**B02C 4/02** (2013.01 - EP US); **B02C 4/28** (2013.01 - EP US); **B30B 3/04** (2013.01 - EP US); **B30B 15/028** (2013.01 - EP); **B30B 15/04** (2013.01 - EP US)

Citation (search report)

See references of WO 2005070549A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

**US 2007187538 A1 20070816; US 7451945 B2 20081118**; AT E371500 T1 20070915; CN 100469450 C 20090318; CN 1913969 A 20070214; DE 202004001187 U1 20050224; DE 502005001375 D1 20071011; DK 1708815 T3 20071112; EP 1708815 A1 20061011; EP 1708815 B1 20070829; WO 2005070549 A1 20050804

DOCDB simple family (application)

**US 58728405 A 20050105**; AT 05700698 T 20050105; CN 200580003214 A 20050105; DE 202004001187 U 20040127; DE 502005001375 T 20050105; DK 05700698 T 20050105; EP 05700698 A 20050105; EP 2005000035 W 20050105