

Title (en)
INTERNAL GEAR PUMP

Title (de)
INNENZAHRADPUMPE

Title (fr)
POMPE A ENGRENAGES INTERIEURS

Publication
EP 1710436 A1 20061011 (EN)

Application
EP 04807610 A 20041222

Priority
• JP 2004019253 W 20041222
• JP 2003435370 A 20031226

Abstract (en)
There is disclosed an internal gear pump in which the sliding resistance of the internal gear pump can be reduced, and the occurrence of noise and a decrease in the pump efficiency can be suppressed to the minimum even in this construction. The internal gear pump includes an inner rotor having external teeth 21, and an outer rotor having internal teeth 11, and draws and discharges fluid to convey the fluid while the inner rotor and the outer rotor rotate in engagement with each other. The internal diameter of a hole 31 formed in a casing 30 for accommodating the inner rotor 10 and the outer rotor 20 is set to be 0.1 mm to 0.6 mm larger than that the external diameter of the outer rotor 20. When "er" is an eccentric distance between the inner rotor 10 and the outer rotor 30 and "eh" is an eccentric distance between the inner rotor 10 and the hole 31 formed in the casing 30, the following inequality is satisfied: $0.005 \text{ mm} \leq (eh - er) \leq 0.030 \text{ mm}$.

IPC 8 full level
F04C 2/10 (2006.01)

CPC (source: EP KR)
F04C 2/10 (2013.01 - KR); **F04C 2/102** (2013.01 - EP); **F04C 2230/602** (2013.01 - EP)

Citation (search report)
See references of WO 2005064163A1

Cited by
US9488172B2

Designated contracting state (EPC)
DE ES FR GB IT

DOCDB simple family (publication)
EP 1710436 A1 20061011; CN 1902401 A 20070124; JP 2005194890 A 20050721; KR 20060129309 A 20061215;
WO 2005064163 A1 20050714

DOCDB simple family (application)
EP 04807610 A 20041222; CN 200480039020 A 20041222; JP 2003435370 A 20031226; JP 2004019253 W 20041222;
KR 20067014980 A 20060725