

Title (en)

Striker

Title (de)

Verriegelungsmulde

Title (fr)

Gâche

Publication

**EP 1724418 A1 20061122 (DE)**

Application

**EP 06405002 A 20060106**

Priority

CH 572005 A 20050114

Abstract (en)

The recess component is in two main parts, a baseplate (1) and cover (2). The baseplate includes a fastening for attachment via a hole (L) in a building component, especially in the floor. A passage (10) gives access to the hole. Mountings (11) are included in the baseplate for two further fastenings (22) in the cover. The cover includes a combined depression and bolt opening (21) which lies above or in the passage (10). The bolt opening (21) is a slot.

IPC 8 full level

**E05B 15/02** (2006.01)

CPC (source: EP)

**E05B 15/0245** (2013.01)

Citation (search report)

- [X] DE 29812639 U1 19990128 - GRETSCH UNITAS GMBH [DE]
- [XA] DE 10146114 A1 20030417 - HEINRICH STRENGER GMBH [DE]
- [A] EP 0801191 A1 19971015 - FERCO INT USINE FERRURES [FR]
- [A] US 4105235 A 19780808 - THIEL FRANK C

Cited by

US11041325B2; EP3190246A1; US10829954B2; US11655654B2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA HR MK YU

DOCDB simple family (publication)

**EP 1724418 A1 20061122**

DOCDB simple family (application)

**EP 06405002 A 20060106**