

Title (en)
Pixel circuit for LCD and method of driving the same

Title (de)
LCD-Pixelschaltung und Ansteuerverfahren dafür

Title (fr)
Circuit de pixels d'un LCD et son procédé

Publication
EP 1724752 A2 20061122 (EN)

Application
EP 06113510 A 20060504

Priority
CN 200510070906 A 20050517

Abstract (en)
A pixel circuit (30) for an active matrix display (3) and the corresponding driving method are disclosed. The pixel circuit comprises a selection transistor (Q 1), a first storage capacitor (C 1), a synchronization unit (202), a second storage capacitor (C 2) and a light emitting element (D). During a scan period, image data is written to the first capacitor (C 1) where it is stored temporarily. Upon reception of a synchronization signal (CN1), the image data is transferred to the second capacitor (C 2) and drives the light emitting element (D). Thus all tight emitting elements (D) are illuminated simultaneously. An additional transistor (Q 2) may be provided for discharging the second capacitor (C 2) and thereby erasing image data of the previous frame before starting a new light emission phase.

IPC 8 full level
G09G 3/22 (2006.01); **G09G 3/32** (2006.01); **G09G 3/36** (2006.01)

CPC (source: EP)
G09G 3/3648 (2013.01); **G09G 3/3659** (2013.01); **G09G 3/32** (2013.01); **G09G 2300/0852** (2013.01); **G09G 2300/0861** (2013.01); **G09G 2310/0251** (2013.01); **G09G 2320/0233** (2013.01); **G09G 2320/0257** (2013.01)

Cited by
EP2472499A1

Designated contracting state (EPC)
DE

Designated extension state (EPC)
AL BA HR MK YU

DOCDB simple family (publication)
EP 1724752 A2 20061122; **EP 1724752 A3 20070808**; CN 1866343 A 20061122

DOCDB simple family (application)
EP 06113510 A 20060504; CN 200510070906 A 20050517