

Title (en)

Locking differential with locking state detection system

Title (de)

Sperrdifferenzial mit Erfassung der Position des Sperrelements

Title (fr)

Différentiel blocable avec un capteur pour la position de l'élément de blocage

Publication

EP 1726851 B1 20081126 (EN)

Application

EP 06010776 A 20060524

Priority

US 13799705 A 20050526

Abstract (en)

[origin: EP1726851A1] A power transmitting device including a housing (24) having an input shaft (20), at least one output shaft (28,30) and a gear set (43) positioned in the housing (24). The gear set (43) transmits rotary power between the input shaft (20) and the output shaft (28,30). An electrical actuator includes a linearly moveable member (54) and is operable to drivingly engage the moveable member (54) with the gear set (43). A sensor (110) is positioned within the housing (24) and operable to output a signal indicative of the linear position of the moveable member (54).

IPC 8 full level

F16H 48/20 (2006.01); **F16H 48/30** (2006.01)

CPC (source: EP KR US)

F16H 48/08 (2013.01 - EP US); **F16H 48/24** (2013.01 - EP US); **F16H 48/30** (2013.01 - EP US); **F16H 48/34** (2013.01 - EP KR US);
B60K 17/16 (2013.01 - EP US); **F16H 2048/204** (2013.01 - EP US); **F16H 2048/346** (2013.01 - EP US)

Cited by

EP2302263A3; EP2002155A4; US7744500B2; US7942780B2; WO2007100545A2; US7878314B2; US7837585B2; US8057345B2; FR3115579A1;
WO2022090328A1; US7682279B2; US7785224B2; US7764154B2; US7825759B2; US7876186B2

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

EP 1726851 A1 20061129; EP 1726851 B1 20081126; BR PI0601931 A 20070213; BR PI0601931 B1 20180515;
DE 602006003808 D1 20090108; KR 101382053 B1 20140404; KR 20060122719 A 20061130; US 2006270508 A1 20061130;
US 7211020 B2 20070501

DOCDB simple family (application)

EP 06010776 A 20060524; BR PI0601931 A 20060526; DE 602006003808 T 20060524; KR 20060046477 A 20060524;
US 13799705 A 20050526