

Title (en)
Extractor for a ball joint

Title (de)
Kugelgelenk-Abdrücker

Title (fr)
Extracteur de rotule

Publication
EP 1733846 B1 20110511 (DE)

Application
EP 06011889 A 20060609

Priority
DE 202005009669 U 20050617

Abstract (en)
[origin: EP1733846A2] Device for pressing a linkage pin of a ball-joint out of the supporting eye of a corresponding axle component comprises a pressing lever (1) and a support lever that are connected together in a pivoting manner via a bearing pin. The pressing lever has a pressing section (2) which, when used, is positioned opposite to a receiving element of the support lever. The pressing section of the pressing lever has a U-shaped cross-section and has two ribs (8, 9) extending towards the receiving element of the support lever and between which the linkage pin is held when it is being pressed on.

IPC 8 full level
B25B 27/02 (2006.01); **B25B 27/073** (2006.01)

CPC (source: EP)
B25B 27/023 (2013.01)

Cited by
US2012272499A1; US9085068B2; JP2009285827A; US11530718B1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1733846 A2 20061220; EP 1733846 A3 20081105; EP 1733846 B1 20110511; AT E508843 T1 20110515; DE 202005009669 U1 20050908

DOCDB simple family (application)
EP 06011889 A 20060609; AT 06011889 T 20060609; DE 202005009669 U 20050617