

Title (en)

LEAK CONTAINER FOR FUEL DISPENSER

Title (de)

LECKAGEBEHÄLTER FÜR BRENNSTOFFABGABEVORRICHTUNG

Title (fr)

CONTENEUR DE FUITE POUR DISTRIBUTEUR DE CARBURANT

Publication

**EP 1737783 A1 20070103 (EN)**

Application

**EP 05725087 A 20050309**

Priority

- US 2005007728 W 20050309
- US 82965904 A 20040422

Abstract (en)

[origin: WO2005108281A1] A leak collection chamber (66) is provided inside the housing (12) of a fuel dispenser (10). The leak collection chamber collects any leaked fuel from fuel handling components inside the fuel dispenser so that the fuel does not leak to the environment. The leak collection chamber can be removed form the fuel dispenser for evacuation. The control system (13) inside the fuel dispenser can determine the liquid level inside the leak containment chamber and generate signals and alarms if the liquid level exceeds a threshold liquid level value and/or the rate of increase in liquid level exceeds a threshold liquid level increase value. The control system can alert service personnel and/or other systems of the leak collection chamber liquid level. Further, the control system and/or other systems shut down the submersible turbine pump that services the fuel dispenser with fuel in response to catastrophe. A leak collection chamber is provided inside the housing of a fuel dispenser. The leak collection chamber collects any leaked fuel from fuel handling components inside the fuel dispenser so that the fuel does not leak to the environment. The leak collection chamber can be removed form the fuel dispenser for evacuation. The control system inside the fuel dispenser can determine the liquid level inside the leak containment chamber and generate signals and alarms if the liquid level exceeds a threshold liquid level value and/or the rate of increase in liquid level exceeds a threshold liquid level increase value. The control system can alert service personnel and/or other systems of the leak collection chamber liquid level. Further, the control system and/or other systems shut down the submersible turbine pump that services the fuel dispenser with fuel in response to catastrophic leak condition.

IPC 8 full level

**B67D 5/32** (2006.01); **B67D 5/64** (2006.01); **B67D 7/32** (2010.01); **B67D 7/84** (2010.01)

CPC (source: EP US)

**B67D 7/04** (2013.01 - EP); **B67D 7/3209** (2013.01 - EP US); **B67D 7/3218** (2013.01 - EP US); **B67D 7/84** (2013.01 - EP US);  
**Y10T 137/0452** (2015.04 - EP US); **Y10T 137/5762** (2015.04 - EP US); **Y10T 137/8342** (2015.04 - EP US)

Citation (search report)

See references of WO 2005108281A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**WO 2005108281 A1 20051117**; EP 1737783 A1 20070103; US 2005236044 A1 20051027; US 2005236045 A1 20051027;  
US 7104278 B2 20060912; US 7111636 B2 20060926

DOCDB simple family (application)

**US 2005007728 W 20050309**; EP 05725087 A 20050309; US 2961005 A 20050105; US 82965904 A 20040422