

Title (en)
DELIVERY UNIT

Title (de)
FÖRDEREINHEIT

Title (fr)
UNITE D'ACHEMINEMENT

Publication
EP 1738068 B1 20110824 (DE)

Application
EP 05707867 A 20050127

Priority
• EP 2005050349 W 20050127
• DE 102004010358 A 20040303

Abstract (en)
[origin: WO2005085623A1] The invention relates to a delivery unit (2) comprising a swirl pot (5), a fuel pump (6) placed therein, and a filter, which is placed on the bottom (7) of the swirl pot (5) and which is radially flowed against. This filter is formed by shaped elements axially protruding from the bottom (7) of the swirl pot (5) whereby forming an axially extending gap (11, 11a, 11b) between every two adjacent shaped elements (10), and the filter surrounds an inlet opening (13) located in the bottom (7) of the swirl pot (5). At least one flow-through area (12) is situated perpendicular to the gaps (11, 11a, 11b) and perpendicular to the flow-through direction, this at least one area (12) connecting at least two adjacent gaps (11, 11a, 11b).

IPC 8 full level
F02M 37/02 (2006.01); **F02M 37/10** (2006.01); **F02M 37/22** (2006.01); **F02M 37/44** (2019.01); **F02M 37/50** (2019.01)

CPC (source: EP KR US)
F02M 37/025 (2013.01 - EP KR US); **F02M 37/106** (2013.01 - EP KR US); **F02M 37/44** (2018.12 - EP US); **F02M 37/50** (2018.12 - EP KR US)

Designated contracting state (EPC)
DE ES FR GB IT

DOCDB simple family (publication)
WO 2005085623 A1 20050915; CN 100472059 C 20090325; CN 1926322 A 20070307; DE 102004010358 B3 20051222; EP 1738068 A1 20070103; EP 1738068 B1 20110824; JP 2007525617 A 20070906; JP 4523636 B2 20100811; KR 101251719 B1 20130405; KR 20060135840 A 20061229; US 2007215537 A1 20070920; US 7350509 B2 20080401

DOCDB simple family (application)
EP 2005050349 W 20050127; CN 200580006551 A 20050127; DE 102004010358 A 20040303; EP 05707867 A 20050127; JP 2007501258 A 20050127; KR 20067020016 A 20050127; US 59118905 A 20050127