

Title (en)
LOCKS

Title (de)
SCHLÖSSER

Title (fr)
SERRURES

Publication
EP 1745187 A4 20140702 (EN)

Application
EP 05735852 A 20050429

Priority
• AU 2005000612 W 20050429
• AU 2004902339 A 20040503

Abstract (en)
[origin: WO2005106166A1] A door lock actuatable by a handle at each side of the door has a lock handing system for rendering selectively operative/inoperative a rotary actuator associated with each handle so that the lock can be operated only from one side of the door as selected. The handing system is formed by screws selectively insertable and removable from outside of the casing prior to installation to lock or permit rotation of the corresponding actuator when a lock member has been moved to a locking position, such as by key actuation.

IPC 8 full level
E05B 63/08 (2006.01); **E05B 13/00** (2006.01); **E05B 13/08** (2006.01); **E05B 55/04** (2006.01); **E05B 55/12** (2006.01); **E05B 63/16** (2006.01); **E05C 1/06** (2006.01); **E05C 1/12** (2006.01); **E05B 17/00** (2006.01); **E05B 63/00** (2006.01)

CPC (source: EP)
E05B 55/12 (2013.01); **E05B 13/004** (2013.01); **E05B 17/005** (2013.01); **E05B 63/0065** (2013.01); **E05B 63/16** (2013.01)

Citation (search report)
• [X] US 6393878 B1 20020528 - FAYNGERSH ZAKHARY [US], et al
• See references of WO 2005106166A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 2005106166 A1 20051110; AU 2005238548 A1 20051110; AU 2005238548 B2 20100701; AU 2010202495 A1 20100708; AU 2010202495 B2 20131003; EP 1745187 A1 20070124; EP 1745187 A4 20140702; NZ 550659 A 20090828; NZ 578602 A 20101126

DOCDB simple family (application)
AU 2005000612 W 20050429; AU 2005238548 A 20050429; AU 2010202495 A 20100615; EP 05735852 A 20050429; NZ 55065905 A 20050429; NZ 57860205 A 20050429