

Title (en)

APPARATUS AND METHOD FOR RECONSTRUCTING A LIGAMENT

Title (de)

GERÄT UND VERFAHREN ZUR REKONSTRUKTION EINES LIGAMENTS

Title (fr)

APPAREIL ET PROCEDE DE RECONSTRUCTION LIGAMENTAIRE

Publication

EP 1746955 A2 20070131 (EN)

Application

EP 05738407 A 20050422

Priority

- US 2005013721 W 20050422
- US 82984604 A 20040422

Abstract (en)

[origin: CN1988859B] A method and apparatus for reconstructing a ligament. In one preferred form of the invention, provided is a graft ligament support block which comprises a body, and a graft hole and a transverse fixation pin hole extending through the body, with both the graft hole and the fixation pin hole preferably extending substantially perpendicular to the longitudinal axis of the body. In one preferred form of the invention, the invention also comprises an installation tool for inserting the graft ligament support block into the bone tunnel and, while supporting the graft ligament support block in the bone tunnel, forming a transverse tunnel in the host bone, with the transverse tunnel in the host bone being aligned with the transverse fixation pin hole in the graft ligament support block. In one preferred method of use, a graft ligament is looped through the graft hole in the graft ligament support block, and the graft ligament support block is mounted to the installation tool. Then the installation tool is used to advance the graft ligament support block through the tibial tunnel, across the interior of the knee joint, and up into the femoral tunnel, with the two free ends of the looped graft ligament extending back out through the tibial tunnel. Next, a transverse tunnel is formed in the host bone, with the transverse tunnel being aligned with the transverse fixation pin hole in the graft ligament support block. Then the graft ligament support block is secured in place by pinning the graft ligament support block within the femoral tunnel, i.e., by advancing a transverse fixation pin along the transverse tunnel in the host bone and into the transverse fixation pin hole in the graft ligament support block. Then the installation tool is detached from the graft ligament support block, and the installation tool is withdrawn from the surgical site.

IPC 8 full level

A61F 2/08 (2006.01); **A61B 17/17** (2006.01)

CPC (source: EP)

A61B 17/1714 (2013.01); **A61F 2/0811** (2013.01)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

AU 2005253927 A1 20051229; AU 2005253927 B2 20101125; CA 2564775 A1 20051229; CA 2564775 C 20130618; CN 101816584 A 20100901; CN 1988859 A 20070627; CN 1988859 B 20100616; EP 1746955 A2 20070131; EP 1746955 A4 20080514; JP 2007534380 A 20071129; JP 2011177524 A 20110915; JP 4879166 B2 20120222; JP 5325257 B2 20131023

DOCDB simple family (application)

AU 2005253927 A 20050422; CA 2564775 A 20050422; CN 200580020199 A 20050422; CN 201010159516 A 20050422; EP 05738407 A 20050422; JP 2007509656 A 20050422; JP 2011091841 A 20110418