

Title (en)
HOUSING COUPLER FOR A COAXIAL PLUG-IN CONNECTOR

Title (de)
GEHÄUSEKUPPLER FÜR EINEN KOAXIALSTECKVERBINDER

Title (fr)
SYSTEME D'ACCOUPLEMENT DE BOITIER POUR CONNECTEUR A FICHE COAXIAL

Publication
EP 1747604 B1 20080305 (DE)

Application
EP 05741073 A 20050511

Priority
• EP 2005005091 W 20050511
• DE 202004007909 U 20040517

Abstract (en)
[origin: CA2533712A1] The invention relates to a coaxial plug (200) for a coaxial plug-in connector, especially of the N-type. Said coaxial plug (200) is provided with a cylindrical outer conductor housing part (36) forming an outer conductor, one end (48) thereof being on the side of the plug and the other end (50) on the side of the coaxial cable. According to the invention, the arrangement is provided with a snap-on sleeve (42) which surrounds the outer conductor housing part (36) and can be axially displaced in relation to the outer conductor housing part (36), and a spring (52) which is supported by one end thereof on the outer conductor housing part (36) and by the other end thereof on the snap-on sleeve (42), such that the snap-on sleeve (42) is prestressed in the direction of the coaxial cable end (50) of the outer conductor housing part (36). The snap-on sleeve (42) is embodied on the plug end (48) thereof with axial slits into which elastic snap-in pins (54) can be inserted, said pins (54) having a radially outwardly raised edge (56) on the plug end thereof. The inventive arrangement is also provided with an unlocking sleeve (44) which surrounds the snap-on sleeve (42) and can be axially displaced in relation thereto (42). Said snap-on sleeve (42) comprises a radially outwardly raised ramp (58) which rises in the direction of the coaxial cable end (50) and co-operates with a correspondingly inclined groove (60) on an inner side of the unlocking sleeve (44), in such a way that a displacement of the unlocking sleeve (44) in relation to the snap-on sleeve (42) in the direction of the coaxial cable end (50) causes the snap-in pins (54) of the snap-on sleeve (42) to radially bend inwards.

IPC 8 full level
H01R 13/627 (2006.01); **H01R 13/631** (2006.01); **H01R 13/633** (2006.01); **H01R 13/646** (2011.01)

CPC (source: EP US)
H01R 13/6277 (2013.01 - EP US); **H01R 13/631** (2013.01 - EP US); **H01R 13/633** (2013.01 - EP US); **H01R 24/40** (2013.01 - EP US); **H01R 2103/00** (2013.01 - EP US)

Cited by
CN106941221A

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
DE 202004007909 U1 20040722; AT E362207 T1 20070615; AT E388508 T1 20080315; CA 2533712 A1 20051201; CA 2533712 C 20120807; CA 2557157 A1 20051201; CA 2557157 C 20090901; CN 100490253 C 20090520; CN 100490254 C 20090520; CN 1788393 A 20060614; CN 1938907 A 20070328; DE 502005000692 D1 20070621; DE 502005003103 D1 20080417; DK 1652275 T3 20070924; DK 1747604 T3 20080707; EP 1652275 A1 20060503; EP 1652275 B1 20070509; EP 1747604 A1 20070131; EP 1747604 B1 20080305; ES 2300018 T3 20080601; HK 1099967 A1 20070831; JP 2007538360 A 20071227; JP 4355015 B2 20091028; US 2007042640 A1 20070222; US 2008261444 A1 20081023; US 7201608 B2 20070410; US 7699651 B2 20100420; WO 2005114794 A1 20051201; WO 2005114795 A1 20051201

DOCDB simple family (application)
DE 202004007909 U 20040517; AT 05741073 T 20050511; AT 05747043 T 20050512; CA 2533712 A 20050512; CA 2557157 A 20050511; CN 200580000388 A 20050512; CN 200580007087 A 20050511; DE 502005000692 T 20050512; DE 502005003103 T 20050511; DK 05741073 T 20050511; DK 05747043 T 20050512; EP 05741073 A 20050511; EP 05747043 A 20050512; EP 2005005091 W 20050511; EP 2005005173 W 20050512; ES 05741073 T 20050511; HK 07107636 A 20070717; JP 2007517030 A 20050511; US 55564705 A 20050512; US 56901905 A 20050511