

Title (en)

METHOD AND DEVICE FOR DRYING PAINTED VEHICLE BODIES

Title (de)

VERFAHREN UND VORRICHTUNG ZUM TROCKNEN VON LACKIERTEN FAHRZEUGKAROSSERIEN

Title (fr)

PROCEDE ET DISPOSITIF DE SECHAGE DE CARROSSERIES DE VEHICULES PEINTES

Publication

EP 1749176 A1 20070207 (DE)

Application

EP 05746458 A 20050512

Priority

- EP 2005005134 W 20050512
- DE 102004025525 A 20040525

Abstract (en)

[origin: WO2005116555A1] The invention relates to a method and a device for drying objects (2) in particular painted vehicle bodies. In said method, the objects (2) are displaced through a drying zone (6), in which they are cured in an inert atmosphere. The aim of the invention is to introduce the objects (2) into the drying zone (8), whilst at the same time preventing the entry of as much of the normal atmosphere of possible from the exterior. To achieve this, the objects (2) are conducted through a lock zone (7), which is located upstream of the drying zone (8) and in which the normal atmosphere lying outside the drying zone (8) and an inert gas atmosphere are present in strata as a result of a difference in densities. The objects (2) are displaced during their passage through the lock zone (7) from the normal atmosphere into the inert gas atmosphere by a motion comprising a vertical component.

IPC 8 full level

F26B 21/14 (2006.01); **F26B 15/08** (2006.01); **F26B 25/00** (2006.01)

CPC (source: EP US)

F26B 15/08 (2013.01 - EP US); **F26B 21/14** (2013.01 - EP US); **F26B 25/008** (2013.01 - EP US); **F26B 2210/12** (2013.01 - EP US)

Citation (search report)

See references of WO 2005116555A1

Designated contracting state (EPC)

DE FR IT SE

DOCDB simple family (publication)

WO 2005116555 A1 20051208; CN 1957217 A 20070502; CN 1957217 B 20101201; DE 102004025525 B3 20051208; DE 502005010010 D1 20100909; EP 1749176 A1 20070207; EP 1749176 B1 20100728; US 2008229608 A1 20080925

DOCDB simple family (application)

EP 2005005134 W 20050512; CN 200580016865 A 20050512; DE 102004025525 A 20040525; DE 502005010010 T 20050512; EP 05746458 A 20050512; US 59739705 A 20050512