

Title (en)
USE OF ALKYLPHENOL-ALDEHYDE RESINS FOR MAKING MINERAL OIL WITH IMPROVED CONDUCTIVITY AND COLD FLOWABILITY

Title (de)
VERWENDUNG VON ALKYLPHENOL-ALDEHYDHARZEN ZUR HERSTELLUNG VON MINERALÖLEN MIT VERBESSERTER LEITFÄHIGKEIT UND KÄLTEFLIESSFÄHIGKEIT

Title (fr)
UTILISATION DE RÉSINES D'ALKYLPHÉNOL-ALDÉHYDE POUR LA PRODUCTION D'HUILES MINÉRALES À CONDUCTIVITÉ ET ÉCOULEMENT À FROID AMÉLIORÉS

Publication
EP 1749874 B1 20180404 (DE)

Application
EP 06013804 A 20060704

Priority
DE 102005035275 A 20050728

Abstract (en)
[origin: EP1749874A2] Improving the electrical conductivity of mineral oil distillate having water content of less than 150 ppm, involves adding a composition which comprises at least one alkylphenolaldehyde resin and 0.10-10 pbw at least one polar oil-soluble nitrogen compound, based on the alkylphenol-aldehyde resin, in such an amount that the mineral oil distillate has a conductivity of at least 50 pS/m. Improving the electrical conductivity of mineral oil distillate having water content of less than 150 ppm, involves adding a composition which comprises at least one alkylphenolaldehyde resin having formula (A) and 0.10-10 pbw at least one polar oil-soluble nitrogen compound, based on the alkylphenol-aldehyde resin, in such an amount that the mineral oil distillate has a conductivity of at least 50 pS/m. R 5>1-200C alkyl or 2-200C alkenyl, O-R 6> or O-C(O)-R 6>; R 6>1-200C-alkyl or 2-200C-alkenyl; n : 2-100. Independent claims are also included for: (1) improving the electrical conductivity of mineral oil distillate having a water content of less than 150 ppm, and comprising 0.1-200 ppm of at least one polar, oil-soluble nitrogen compound, comprising adding to the mineral oil distillate 0.1-200 ppm of at least one alkylphenol-aldehyde resin (A), so that the mineral oil distillate have a conductivity of at least 50 pS/m; and (2) mineral oil distillate having an aromatics content of less than 21 wt.%, a water content of less than 150 ppm, and a conductivity of at least 50 pS/m, and comprising 0.1-200 pm of at least one alkylphenol-aldehyde resin (A). [Image].

IPC 8 full level
C10L 1/14 (2006.01); **C10L 1/198** (2006.01); **C10L 1/236** (2006.01); **C10L 1/238** (2006.01); **C10L 1/2383** (2006.01); **C10L 1/2387** (2006.01); **C10L 10/10** (2006.01); **C10L 10/14** (2006.01)

CPC (source: EP KR US)
C10L 1/143 (2013.01 - EP KR US); **C10L 1/16** (2013.01 - KR); **C10L 1/22** (2013.01 - KR); **C10L 10/14** (2013.01 - EP KR US); **C10M 101/00** (2013.01 - KR); **C10L 1/1641** (2013.01 - EP US); **C10L 1/1835** (2013.01 - EP US); **C10L 1/195** (2013.01 - EP US); **C10L 1/1981** (2013.01 - EP US); **C10L 1/1985** (2013.01 - EP US); **C10L 1/221** (2013.01 - EP US); **C10L 1/2222** (2013.01 - EP US); **C10L 1/2225** (2013.01 - EP US); **C10L 1/224** (2013.01 - EP US); **C10L 1/2364** (2013.01 - EP US); **C10L 1/2383** (2013.01 - EP US); **C10L 1/2475** (2013.01 - EP US); **C10L 2230/20** (2013.01 - KR)

Cited by
EP1985685A1; WO2008107371A3; US8551365B2; US8858838B2; US10062471B2; EP4074810B1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1749874 A2 20070207; **EP 1749874 A3 20090916**; **EP 1749874 B1 20180404**; **EP 1749874 B8 20180919**; CA 2554359 A1 20070128; CA 2554359 C 20140909; CN 1904007 A 20070131; CN 1904007 B 20110817; DE 102005035275 A1 20070208; DE 102005035275 B4 20071011; HU E038970 T2 20181228; JP 2007031717 A 20070208; JP 5382984 B2 20140108; KR 20070015080 A 20070201; KR 20140061329 A 20140521; PL 1749874 T3 20180731; RU 2006127365 A 20080210; RU 2419651 C2 20110527; US 2007027041 A1 20070201; US 8283298 B2 20121009

DOCDB simple family (application)
EP 06013804 A 20060704; CA 2554359 A 20060727; CN 200610100098 A 20060629; DE 102005035275 A 20050728; HU E06013804 A 20060704; JP 2006204697 A 20060727; KR 20060071489 A 20060728; KR 20140036965 A 20140328; PL 06013804 T 20060704; RU 2006127365 A 20060727; US 49495106 A 20060728