

Title (en)

AGGLOMERATED STONE FOR USING IN SHAFT FURNACES, COREX FURNACES OR BLAST FURNACES, METHOD FOR PRODUCING AGGLOMERATED STONES, AND USE OF FINE AND SUPERFINE IRON ORE DUST

Title (de)

AGGLOMERATSTEIN ZUM EINSATZ IN SCHACHT-, COREX- ODER HOCHÖFEN, VERFAHREN ZUR HERSTELLUNG VON AGGLOMERATSTEINEN UND VERWENDUNG VON EISENERZ-FEIN- UND -FEINSTSTÄUBEN

Title (fr)

PIERRE AGGLOMEREE POUR FOIRS A CUVE, FOIRS COREX ET HAUTS FOURNEAUX, PROCEDE POUR FABRIQUER CETTE PIERRE AGGLOMEREE ET UTILISATION DE POUSSIERES DE MINERAIS DE FER FINES ET HYPERFINES

Publication

EP 1753884 A1 20070221 (DE)

Application

EP 05745341 A 20050525

Priority

- EP 2005005626 W 20050525
- DE 102004027193 A 20040603

Abstract (en)

[origin: WO2005118892A1] The aim of the invention is to be able to economically use ore dust which is created by the extraction and preparation of iron ore and has not been usable until now. To this end, the invention relates to an agglomerated stone comprising (in wt. %) between 6 and 15 % of a cement binding agent, up to 20 % of a carbon carrier, up to 20 % of residual and recyclable substances, and optionally up to 10 % of an accelerator, the remainder consisting of iron ore in a stone format in the form of particles having a particle size of less than 3 mm. After three days, the iron ore has an initial strength of at least 5 N/mm², and after 28 days, a cold compression strength of at least 20 N/mm². As a result of the particular hardness St and form stability thereof even at high temperatures T, inventive agglomerated stones are especially suitable for using in shaft furnaces, corex furnaces, or blast furnaces. The invention also relates to a method for producing inventive agglomerated stones.

[origin: WO2005118892A1] Agglomerated stone comprising (wt. %): cement binding agent (6-15), carbon carrier (up to 20), residual and recyclable substances (up to 20), and optionally accelerator (up to 10), remainder iron ore stone in the form of particles of grain size below 3 mm. After 3 days the iron ore has an initial strength of at least 5 N/mm² and after 28 days a cold compression strength of at least 20 N/mm². An independent claim is included for a method of preparing the stone as described above by transfer of the composition to a mold and compacting.

IPC 8 full level

C22B 1/243 (2006.01); **C22B 7/02** (2006.01); **F27D 1/00** (2006.01); **F27D 1/04** (2006.01); **C22B 1/00** (2006.01)

CPC (source: EP US)

C22B 1/243 (2013.01 - EP US); **C22B 7/02** (2013.01 - EP US); **F27D 1/0006** (2013.01 - EP US); **F27D 1/04** (2013.01 - EP US);
C22B 1/00 (2013.01 - EP US); **Y02P 10/20** (2015.11 - EP US)

Citation (search report)

See references of WO 2005118892A1

Citation (examination)

- US 2004025633 A1 20040212 - KANOSHIMA HIDEO [JP], et al
- GB 1445792 A 19760811 - NIPPON STEEL CORP
- US 3490895 A 19700120 - SVENSSON KARL JONAS V
- DE 3139375 A1 19830414 - MUEHLBERGER HORST DIPL PHYS DR

Designated contracting state (EPC)

DE SE

DOCDB simple family (publication)

WO 2005118892 A1 20051215; AU 2005250105 A1 20051215; AU 2005250105 B2 20100722; BR PI0511806 A 20080115;
CA 2569247 A1 20051215; CN 1961085 A 20070509; DE 102004027193 A1 20051229; EP 1753884 A1 20070221; RU 2006146980 A 20080720;
RU 2366735 C2 20090910; UA 87686 C2 20090810; US 2008250980 A1 20081016; US 8025727 B2 20110927

DOCDB simple family (application)

EP 2005005626 W 20050525; AU 2005250105 A 20050525; BR PI0511806 A 20050525; CA 2569247 A 20050525;
CN 200580017868 A 20050525; DE 102004027193 A 20040603; EP 05745341 A 20050525; RU 2006146980 A 20050525;
UA A200612702 A 20050525; US 62835205 A 20050525