

Title (en)

Quick upper tool coupling and uncoupling device of a press brake

Title (de)

Schnelle Kupplungs- und Unkupplungs-Vorrichtung für das Oberwerkzeug einer Biegepresse

Title (fr)

Dispositif de couplage et découplage rapide pour un outil supérieur d'une presse plieuse

Publication

EP 1762310 A1 20070314 (EN)

Application

EP 05425638 A 20050913

Priority

EP 05425638 A 20050913

Abstract (en)

The rapid coupling and uncoupling device consists essentially of a plunger element 12 capable of being inserted into the clamp 4 or into the top beam/intermediary 1 of the press brake, or into the tool connection 2, having a cursor 14 with a terminal part of a tapered form pressed by a spring to engage within a groove 16 present in the tool connection or in the clamp or in the top beam/intermediary, respectively.

IPC 8 full level

B21D 5/02 (2006.01)

CPC (source: EP)

B21D 5/0209 (2013.01); **B21D 5/0236** (2013.01)

Citation (applicant)

EP 0494714 A1 19920715 - WILA MASCHF BV [NL]

Citation (search report)

- [XY] JP H06182447 A 19940705 - AMADA METRECS CO
- [Y] DE 3524694 A1 19870122 - HILMA GMBH MASCHF [DE]
- [Y] JP H10277647 A 19981020 - AMADA METRECS CO
- [AD] EP 0494714 A1 19920715 - WILA MASCHF BV [NL]
- [XY] PATENT ABSTRACTS OF JAPAN vol. 018, no. 524 (M - 1682) 4 October 1994 (1994-10-04)
- [Y] PATENT ABSTRACTS OF JAPAN vol. 1999, no. 01 29 January 1999 (1999-01-29)

Cited by

ITVR20100202A1; ITBO20090540A1; CN109702070A; CN104138939A; ITMI20100110A1; CN104259260A; NL2009340C2; CN104507596A; JP2018134684A; US10883249B2; US10144049B2; IT202200015465A1; WO2012052942A1; WO2014007640A1; WO2011092558A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA HR MK YU

DOCDB simple family (publication)

EP 1762310 A1 20070314; EP 1762310 B1 20071114; AT E378122 T1 20071115; DE 602005003366 D1 20071227; DE 602005003366 T2 20080221; ES 2296121 T3 20080416; PL 1762310 T3 20080430

DOCDB simple family (application)

EP 05425638 A 20050913; AT 05425638 T 20050913; DE 602005003366 T 20050913; ES 05425638 T 20050913; PL 05425638 T 20050913