

Title (en)
HYDRAULIC CYLINDER

Title (de)
HYDRAULIKZYLINDER

Title (fr)
VERIN HYDRAULIQUE

Publication
EP 1766247 A1 20070328 (EN)

Application
EP 05742443 A 20050506

Priority
• GB 2005001706 W 20050506
• GB 0410848 A 20040514

Abstract (en)
[origin: WO2005111432A1] A hydraulic cylinder (10) is disclosed. The hydraulic cylinder has a tube (20) provided with a cap (30) attached to a first axial end portion of the tube (20) and a head (40) attached to the other axial end portion of the tube (20). A piston (55) is slideable axially within the tube (20) and is arranged to seal against the inside surface of the tube as it slides. The piston (55) has a rod (60) attached thereto which passes through and seals against the head (40) as it moves with the piston (55). Conduits (31, 41) are provided to be connected, in use, to sources of hydraulic fluid via suitable supply lines to control fluid pressure on at least one side of the piston (55) within the tube (20) to control axial movement of the piston (55) within the tube (20). End portions (21, 22) of the tube (20) are mechanically formed into engagement with at least one of the cap (30) and the head (40) to fix the tube in a permanent and fluid tight manner thereto. A method of assembling a hydraulic cylinder (10) is also disclosed.

IPC 8 full level
F15B 15/14 (2006.01)

CPC (source: EP)
F15B 15/1433 (2013.01); **F15B 15/1438** (2013.01)

Citation (search report)
See references of WO 2005111432A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 2005111432 A1 20051124; EP 1766247 A1 20070328; GB 0410848 D0 20040616; GB 2414043 A 20051116

DOCDB simple family (application)
GB 2005001706 W 20050506; EP 05742443 A 20050506; GB 0410848 A 20040514