

Title (en)  
BREAKER DEVICE FOR LOW VOLTAGE APPLICATIONS

Title (de)  
SCHALTGERÄT FÜR NIEDERSpannungsANWENDUNGEN

Title (fr)  
DISPOSITIF DE COMMUTATION DESTINE A DES APPLICATIONS BASSE TENSION

Publication  
**EP 1771870 B1 20121226 (DE)**

Application  
**EP 05763086 A 20050726**

Priority  
• EP 2005053642 W 20050726  
• DE 102004036279 A 20040727

Abstract (en)  
[origin: WO2006010760A1] In breaker devices an early short-circuit recognition is required and also a tripping of the contacts. According to the invention, the recognition of a short-circuit occurs so early that with consideration of the response time of the measuring probes and the unlocking mechanism (5, 6-8) by a suitable analysis algorithm the release of the moving contact (4) occurs before or at least at the time that the current-breaking forces correspond to the contact force. The contact force is hence compensated for and a rapid opening of the contacts (2, 4) can be achieved.

IPC 8 full level  
**H01H 71/24** (2006.01); **H01H 71/43** (2006.01); **H02H 3/08** (2006.01); **H02H 3/44** (2006.01)

CPC (source: EP US)  
**H01H 71/2418** (2013.01 - EP US); **H01H 71/43** (2013.01 - EP US); **H01H 3/222** (2013.01 - EP US); **H01H 71/123** (2013.01 - EP US)

Designated contracting state (EPC)  
DE FR GB IT

DOCDB simple family (publication)  
**WO 2006010760 A1 20060202**; CN 1993790 A 20070704; CN 1993790 B 20111012; DE 102004036279 A1 20060323;  
EP 1771870 A1 20070411; EP 1771870 B1 20121226; US 2009046403 A1 20090219; US 7916442 B2 20110329

DOCDB simple family (application)  
**EP 2005053642 W 20050726**; CN 200580025635 A 20050726; DE 102004036279 A 20040727; EP 05763086 A 20050726;  
US 65883805 A 20050726