

Title (en)

Method for the detection of a configuration of a plurality of lifting arrangements of a lifting system

Title (de)

Verfahren zum Erfassen einer Konfiguration von mehreren Hubeinrichtungen in einem Hubsystem

Title (fr)

Méthode de détection de la configuration de plusieurs dispositives de levage dans un système de levage

Publication

EP 1775253 B1 20101222 (DE)

Application

EP 06021170 A 20061010

Priority

DE 102005049002 A 20051011

Abstract (en)

[origin: EP1775253A2] The method involves selection of number of lifting devices for lifting a load (14) and can be connected together in series through supply line (21). The control of the lifting devices in the lifting system (11) can be initialized by a control line. Lifting device is positioned at an open end of the series, a level is simulated at the inlet of the controller (19) and first node address is generated and stored. The lifting device is defined as the master lifting device with the first node address. Afterwards an outlet of the controller of the first lifting device is switched and a level lies at an inlet of the following lifting device (12b, 13b) and an incremental node address in the following lifting device is generated and stored. The first lifting device notifies a signal, so that the lifting device stores the assigned node address.

IPC 8 full level

B66F 3/46 (2006.01); **B66F 7/20** (2006.01)

CPC (source: EP US)

B66F 3/46 (2013.01 - EP US); **B66F 7/20** (2013.01 - EP US); **Y10T 137/2516** (2015.04 - EP US)

Designated contracting state (EPC)

DE FR GB IT NL

DOCDB simple family (publication)

EP 1775253 A2 20070418; EP 1775253 A3 20070425; EP 1775253 B1 20101222; DE 102005049002 A1 20070412;
DE 502006008545 D1 20110203; US 2007096068 A1 20070503; US 7644807 B2 20100112

DOCDB simple family (application)

EP 06021170 A 20061010; DE 102005049002 A 20051011; DE 502006008545 T 20061010; US 54579206 A 20061010