

Title (en)
ELECTRODE ADDRESSING METHOD

Title (de)
ELEKTRODENADRESSIERUNGSVERFAHREN

Title (fr)
METHODE D'ADRESSAGE D'ELECTRODES

Publication
EP 1778976 A2 20070502 (FR)

Application
EP 05789844 A 20050711

Priority
• FR 2005050570 W 20050711
• FR 0451494 A 20040709

Abstract (en)
[origin: WO2006008424A2] The invention relates to a device for addressing an electrode array comprising 2ⁿ lines of an electro-fluidic device, whereby each line contains N electrodes ($n \leq N$). The inventive device comprises: on each line, n selection electrodes (Esl - i), whereby all of said line selection electrodes are connected to 2n line selection conductors (Cl, Cl', C2, C2', C3, C3') and 2ⁿ⁻¹ line selection electrodes of 2ⁿ⁻¹ lines are connected to each line selection conductor; and selection means (Rsl-k, Rsl-k') which are used to select one or more line selection conductors.

IPC 8 full level
F04B 19/00 (2006.01); **B01F 13/00** (2006.01)

CPC (source: EP US)
B01F 33/3021 (2022.01 - EP US); **B01F 33/3031** (2022.01 - EP US); **F04B 19/006** (2013.01 - EP US); **B01L 2300/089** (2013.01 - EP US)

Citation (search report)
See references of WO 2006008424A2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
FR 2872809 A1 20060113; **FR 2872809 B1 20060915**; AT E389113 T1 20080315; DE 602005005337 D1 20080424;
DE 602005005337 T2 20090326; EP 1778976 A2 20070502; EP 1778976 B1 20080312; JP 2008505631 A 20080228; JP 4814230 B2 20111116;
US 2009192044 A1 20090730; US 8603413 B2 20131210; WO 2006008424 A2 20060126; WO 2006008424 A3 20060413

DOCDB simple family (application)
FR 0451494 A 20040709; AT 05789844 T 20050711; DE 602005005337 T 20050711; EP 05789844 A 20050711; FR 2005050570 W 20050711;
JP 2007519856 A 20050711; US 63099905 A 20050711