

Title (en)

Method and device for idle discharge of an inkjet printhead

Title (de)

Verfahren und Vorrichtung zum Freispritzen eines Tintendruckkopfes

Title (fr)

Méthode et dispositif de purge d'une tête d'impression à jet d'encre

Publication

EP 1782955 B1 20120125 (DE)

Application

EP 06021927 A 20061019

Priority

DE 102005052151 A 20051102

Abstract (en)

[origin: EP1782955A1] The method involves relatively moving a parallel unit (4) in a flat area or in a layer parallel to a nozzle surface of an ink print head in connection with a free-injection of the print head. Ink drops ejected from the print head are redirected in motion of drops by a fast rotating movement of a disc (40) or the parallel unit during the free-injection of the print head, where the print head is moved during the free-injection. An independent claim is also included for a device for free-injection of an ink print head of an ink print system.

IPC 8 full level

B41J 2/165 (2006.01); **G07B 17/00** (2006.01)

CPC (source: EP US)

B41J 2/16505 (2013.01 - EP US); **B41J 2/1742** (2024.05 - EP); **G07B 17/00508** (2013.01 - EP US); **B41J 2/1742** (2024.05 - US); **G07B 2017/00532** (2013.01 - EP US); **G07B 2017/00556** (2013.01 - EP US)

Cited by

DE102007035875B3; EP2020299A3; EP2020299A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1782955 A1 20070509; **EP 1782955 B1 20120125**; AT E542674 T1 20120215; DE 102005052151 B3 20070531; US 2007120886 A1 20070531; US 7645021 B2 20100112

DOCDB simple family (application)

EP 06021927 A 20061019; AT 06021927 T 20061019; DE 102005052151 A 20051102; US 49704606 A 20060801