

Title (en)
Electrical circuit for an LED signal lamp with a switching threshold for switching between a daylight operation mode and a nighttime operation mode

Title (de)
Elektrische Schaltung für LED Signallampen mit einer Schaltschwelle zum Umschalten zwischen Tages- und Nachtbetrieb

Title (fr)
Circuit électrique pour des lampes de signalisation avec diodes électroluminescentes ayant un seuil pour changer entre un mode de fonctionnement de jour et un mode de fonctionnement de nuit

Publication
EP 1787886 A1 20070523 (EN)

Application
EP 05292461 A 20051118

Priority
EP 05292461 A 20051118

Abstract (en)
An electrical circuit (1, 21) for operating a signal lamp (5), with a signal lamp (5) comprising at least one light emitting diode (D3, D4, D5, D6), with a voltage input (V1) for supplying the electrical circuit (1, 21) with AC voltage, and with a diode (D1) connected in series with the voltage input (V1), is characterized in that the electrical circuit (1, 21) comprises a first subcircuit (11) connecting the cathode (4) of the diode (D1) with the signal lamp (5), that the electrical circuit (1, 21) comprises a second subcircuit (12a, 12b) providing a low resistance current path (R6, R7, Q1) in parallel to the signal lamp (5), as compared to the signal lamp (5), when the AC voltage is below a first critical level, that the electrical current (1; 21) comprises a third subcircuit (13) disabling the low resistance current path (R6, R7, Q1) in parallel to the signal lamp (5), as compared to the signal lamp (5), when the AC voltage is above the first critical level, and that the electrical circuit (1, 21) comprises a fourth subcircuit (14) providing a low resistance connection (M1, R3, R4) from cathode (4) of the diode (D1) to the signal lamp (5), as compared to the first subcircuit (11), when the AC voltage is above a second critical level (scl). The inventive electrical circuit allows an adaptation of the luminous intensity by varying the AC input voltage.

IPC 8 full level
B61L 5/18 (2006.01); **G08G 1/095** (2006.01); **H05B 44/00** (2022.01)

CPC (source: EP US)
B61L 5/1881 (2013.01 - EP US); **H05B 45/00** (2020.01 - EP US); **H05B 45/10** (2020.01 - EP US); **H05B 45/3574** (2020.01 - EP US); **B61L 2207/02** (2013.01 - EP)

Citation (search report)

- [A] EP 0992961 A2 20000412 - SIEMENS AG [DE]
- [A] WO 9512512 A1 19950511 - SIEMENS INTEGRA VERKEHRSTECHNI [CH]
- [A] WO 03096753 A1 20031120 - SIEMENS AG [DE], et al
- [A] US 2005029961 A1 20050210 - POPLOW NORBERT [DE], et al
- [A] EP 1324641 A2 20030702 - WESTINGHOUSE BRAKE & SIGNAL [GB]
- [A] ZABEL M ET AL: "LED - EINE NEUE GENERATION VON LICHTQUELLEN FUER EISENBAHNSIGNALE", SIGNAL + DRAHT, TELZLAFF VERLAG GMBH. DARMSTADT, DE, no. 9, September 2000 (2000-09-01), pages 31 - 30, XP009033674, ISSN: 0037-4997

Cited by
EP2445318A1; EP2146551A3; CN116437201A; DE102008025187A1; EP2463174A1; WO2012076313A1; WO2013045867A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA HR MK YU

DOCDB simple family (publication)
EP 1787886 A1 20070523; **EP 1787886 B1 20080102**; AT E382530 T1 20080115; CN 100581308 C 20100113; CN 1968554 A 20070523; DE 602005004167 D1 20080214; DE 602005004167 T2 20081224

DOCDB simple family (application)
EP 05292461 A 20051118; AT 05292461 T 20051118; CN 200610148497 A 20061117; DE 602005004167 T 20051118