

Title (en)
VEHICLE LEVEL DETECTION

Title (de)
FAHRZEUGNIVEAUERFASSUNG

Title (fr)
DETECTION D'ASSIETTE DE VEHICULE

Publication
EP 1789269 A1 20070530 (DE)

Application
EP 05788568 A 20050914

Priority
• DE 2005001606 W 20050914
• DE 102004045670 A 20040917

Abstract (en)
[origin: WO2006029602A1] The invention relates to a device for measuring the state of compression of a motor vehicle comprising a plurality of axial parts (3) and a chassis (2) between which spring elements (1) are arranged, in addition to at least one magnet arrangement (7) and at least one magnet field sensor (8) which is displaced in relation to the magnet arrangement (7) during a modification of the state of compression of the motor vehicle. The magnet arrangement (7) or the magnet field sensor (8) is arranged on one area of the spring element (1) which displaces, during modification of the state of compression, and also in relation to the chassis (2) and in relation to the axial part (3).

IPC 8 full level
B60G 17/00 (2006.01)

CPC (source: EP KR US)
B60G 11/48 (2013.01 - EP US); **B60G 17/015** (2013.01 - KR); **B60G 17/019** (2013.01 - KR); **B60G 17/01933** (2013.01 - EP US);
G01D 5/145 (2013.01 - EP US); **G01D 5/16** (2013.01 - KR); **G01D 5/20** (2013.01 - KR); **B60G 2200/144** (2013.01 - EP US);
B60G 2204/11 (2013.01 - EP US); **B60G 2400/252** (2013.01 - EP US); **B60G 2401/172** (2013.01 - EP US)

Citation (search report)
See references of WO 2006029602A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
DE 102004045670 B3 20060209; CN 101027199 A 20070829; EP 1789269 A1 20070530; JP 2008513264 A 20080501;
KR 20070064615 A 20070621; US 2008099967 A1 20080501; WO 2006029602 A1 20060323

DOCDB simple family (application)
DE 102004045670 A 20040917; CN 200580031171 A 20050914; DE 2005001606 W 20050914; EP 05788568 A 20050914;
JP 2007531588 A 20050914; KR 20077007675 A 20070404; US 57542405 A 20050914