

Title (en)
YARN FEEDING DEVICE

Title (de)
FADENZUFÜHRUNGSVORRICHTUNG

Title (fr)
DISTRIBUTEUR DE FIL

Publication
EP 1796994 A1 20070620 (EN)

Application
EP 05787261 A 20050916

Priority
• EP 2005010003 W 20050916
• DE 102004049211 A 20041008

Abstract (en)
[origin: WO2006037451A1] A yarn feeding device F has a housing 1 supporting a drive shaft 10 which carries a stationary storage body K. the storage body K consists of a supporting rod cage 5 which is coaxial to the drive shaft 10 which is rotatably supported on the drive shaft 10, and a separation rod cage 7 which is rotatably supported on a separation rod cage bearing structure L. The axis Y of the separation rod cage 7 is inclined and eccentric in relation to the axis X of the drive shaft 10. In the separation rod cage bearing structure L as well is eccentric and inclined in relation to the axis X of the drive shaft. The eccentricity E of the separation rod cage bearing structure L is offset in circumferential direction in relation to the inclination S. The separation rod cage bearing structure L is connected to the drive shaft 10 such that the rod cage bearing structure L is integrally formed at the drive shaft 10.

IPC 8 full level
D04B 15/48 (2006.01)

CPC (source: EP)
D04B 15/482 (2013.01)

Citation (search report)
See references of WO 2006037451A1

Cited by
DE102018115631A1; EP3587643A1

Designated contracting state (EPC)
IT

DOCDB simple family (publication)
WO 2006037451 A1 20060413; CN 101052579 A 20071010; CN 101052579 B 20120307; DE 102004049211 A1 20060420; EP 1796994 A1 20070620; EP 1796994 B1 20090429

DOCDB simple family (application)
EP 2005010003 W 20050916; CN 200580033324 A 20050916; DE 102004049211 A 20041008; EP 05787261 A 20050916