

Title (en)  
FITTING FOR A TURNING WINDOW AND TURNING WINDOW WITH SUCH A FITTING

Title (de)  
BESCHLAG FÜR EIN WENDEFENSTER UND WENDEFENSTER MIT EINEM SOLCHEN BESCHLAG

Title (fr)  
FERRURE POUR FENÊTRE BATTANTE ET FENÊTRE BATTANTE AVEC UNE TELLE FERRURE

Publication  
**EP 1802837 B1 20110323 (DE)**

Application  
**EP 05793980 A 20051020**

Priority  
• CH 2005000616 W 20051020  
• CH 17372004 A 20041020  
• CH 6732005 A 20050414

Abstract (en)  
[origin: WO2006042438A2] The invention relates to a fitting for a turning window and to the turning window comprising a fitting. The turning window (11) comprises a frame (15) and a window leaf (17) which can be turned in relation to the frame (15). In order to turn the window wing (17), the first end thereof can be displaceably mounted along the frame (15) which can be displaced from a closing position of the window leaf (17) on a first end of the frame (15) into an open position from the first end of the frame (15). The window leaf (17) is supported by an adjustment plate (41) which is at least approximately in equilibrium. The fitting (13) comprises a frame guiding rail (31) which is secured to the frame (15), a displacement part (35) which can be guided by the guiding rail (31) from the closed position until the open position. The displacement part is articulated in a pivotable manner to one end of the window leaf (17) about the displaceable axis (51). The first side of the adjustment plate (41) is formed by an arm (39) which is articulated with a balance axis (55) on the window leaf (17). The second side is formed by two equidirectional pivotable levers (61, 63) which are articulated on an arm (39) by means of two jointed axes (75, 77) which are arranged at a distance from each other. Said pivotable levers are articulated by means of two articulated axes (71, 73) on points on the frame (15), said points being arranged at a distance from each other. In said type of turning windows, the pivotable lever (61, 63) extends from the jointed axes (75, 77) to the articulated axes (71, 73) and also the arm (39) extends from the jointed axes (75, 77) to the balance axes (55) in the direction to the closing position of the displacement part (35).

IPC 8 full level  
**E05D 15/44** (2006.01)

CPC (source: EP)  
**E05D 15/44** (2013.01); **E05Y 2900/148** (2013.01)

Cited by  
EP3409869A1

Designated contracting state (EPC)  
AT BE BG CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**WO 2006042438 A2 20060427; WO 2006042438 A3 20060803**; AT E503072 T1 20110415; CA 2629887 A1 20060427; DE 502005011167 D1 20110505; EP 1802837 A2 20070704; EP 1802837 B1 20110323

DOCDB simple family (application)  
**CH 2005000616 W 20051020**; AT 05793980 T 20051020; CA 2629887 A 20051020; DE 502005011167 T 20051020; EP 05793980 A 20051020