

Title (en)

Printing unit having a transfer cylinder with different amplitudes for throw-off and corresponding throw-on positions

Title (de)

Druckeinheit deren Übertragungszylinder unterschiedliche Amplituden für Druck-Abstimmung und entsprechend für die Druck-Anstellung aufweist

Title (fr)

Unité d'impression à amplitudes différentes de déplacement des cylindres porte-blanchet pour atteindre une configuration hors-pression et presse d'impression correspondante

Publication

EP 1803559 B1 20110713 (FR)

Application

EP 06291946 A 20061215

Priority

FR 0513377 A 20051227

Abstract (en)

[origin: EP1803559A1] One printing unit (8) has two configurations where the two blanket cylinders are pressed against each other and against the plate cylinders (24A-B) in the throw-on configuration and the blanket cylinders are spaced apart from each other in the throw-off configuration. In the throw-off configuration, the upper blanket cylinder (22A) is raised relative to its position in a throw-on configuration, and the lower blanket cylinder (22B) is lowered relative to its position in a throw-on configuration. The cylinders are moved by a support and movement mechanism (26).

IPC 8 full level

B41F 13/24 (2006.01); **B41F 13/34** (2006.01); **B41F 13/36** (2006.01); **B41F 13/38** (2006.01); **B41F 13/40** (2006.01); **B41F 33/04** (2006.01); **B41F 33/18** (2006.01)

CPC (source: EP US)

B41F 13/02 (2013.01 - EP US); **B41F 13/32** (2013.01 - EP US); **B41F 13/36** (2013.01 - EP US); **B41F 13/40** (2013.01 - EP US)

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

EP 1803559 A1 20070704; **EP 1803559 B1 20110713**; CN 101003198 A 20070725; CN 101003198 B 20120926; FR 2895306 A1 20070629; FR 2895306 B1 20080404; JP 2007176176 A 20070712; US 2007144370 A1 20070628; US 7823506 B2 20101102

DOCDB simple family (application)

EP 06291946 A 20061215; CN 200610156770 A 20061227; FR 0513377 A 20051227; JP 2006352596 A 20061227; US 64503106 A 20061222