

Title (en)
Display device

Title (de)
Anzeigevorrichtung

Title (fr)
Dispositif d'affichage

Publication
EP 1808844 B1 20121031 (EN)

Application
EP 07000060 A 20070103

Priority
JP 2006005592 A 20060113

Abstract (en)
[origin: EP1808844A2] A display device is proposed in which scan line driver circuits are not disposed on opposite sides of a scan line, but one end of the scan line is driven by a scan line driver circuit, while the other end of the scan line is driven by a scan line auxiliary circuit which has a significantly smaller circuit scale and lower power consumption than the scan line driver circuit. The scan line auxiliary circuit is controlled with a selection pulse of the scan line or a signal of the scan line driver circuit, and is electrically connected to a fixed potential through a transistor. When a potential of the scan line is switched by the scan line driver circuit, the scan line auxiliary circuit operates so that the scan line is driven from its opposite ends.

IPC 8 full level
G09G 3/32 (2006.01); **H05B 44/00** (2022.01)

CPC (source: EP US)
G09G 3/3233 (2013.01 - EP US); **G09G 3/3266** (2013.01 - EP US); **G09G 2300/0819** (2013.01 - EP US); **G09G 2300/0842** (2013.01 - EP US); **G09G 2310/0251** (2013.01 - EP US); **G09G 2310/0262** (2013.01 - EP US); **G09G 2310/061** (2013.01 - EP US); **G09G 2320/0223** (2013.01 - EP US); **G09G 2320/029** (2013.01 - EP US); **G09G 2320/041** (2013.01 - EP US); **G09G 2320/043** (2013.01 - EP US); **G09G 2330/021** (2013.01 - EP US)

Cited by
US8519628B2

Designated contracting state (EPC)
DE FI FR GB NL

DOCDB simple family (publication)
EP 1808844 A2 20070718; **EP 1808844 A3 20090304**; **EP 1808844 B1 20121031**; CN 101000747 A 20070718; CN 101000747 B 20120801; US 2007164967 A1 20070719; US 7777710 B2 20100817

DOCDB simple family (application)
EP 07000060 A 20070103; CN 200710001711 A 20070112; US 65228207 A 20070111