

Title (en)

METHOD FOR ELECTROLYTIC MACHINING A WORKPIECE HAVING A THROUGH HOLE.

Title (de)

VERFAHREN ZUR ELEKTROLYTISCHEN BEARBEITUNG EINES BAUTEILS MIT DURCHGANGSLOCH

Title (fr)

MÉTHODE D'USINAGE ÉLECTROLYTIQUE D'UNE PIÈCE DE TRAVAIL AYANT UN TROU TRAVERSANT.

Publication

EP 1809435 A1 20070725 (DE)

Application

EP 05786982 A 20050916

Priority

- EP 2005054614 W 20050916
- EP 04026621 A 20041109
- EP 05786982 A 20050916

Abstract (en)

[origin: EP1655092A1] An electrolytic treatment method for a component having at least two through-holes (7, 7', 7", 7'', 7''', 7''") involves treating (specifically coating) the interior surfaces (8, 8', 8", 8'', 8''', 8''") of the holes using separate pole electrodes (19, 19', 19", 19'''), having the same polarity. An independent claim is included for a component with at least two through-holes produced by the process.

IPC 8 full level

B23H 9/00 (2006.01); **B23H 9/10** (2006.01); **B23H 9/14** (2006.01); **B23H 9/16** (2006.01); **C25D 3/60** (2006.01); **C25D 5/10** (2006.01)

CPC (source: EP US)

B23H 9/00 (2013.01 - EP US); **B23H 9/10** (2013.01 - EP US); **B23H 9/14** (2013.01 - EP US); **B23H 9/16** (2013.01 - EP US);
C25D 5/026 (2013.01 - EP US); **C25D 7/04** (2013.01 - EP US); **C25F 3/14** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1655092 A1 20060510; EP 1809435 A1 20070725; US 2009208344 A1 20090820; WO 2006051019 A1 20060518

DOCDB simple family (application)

EP 04026621 A 20041109; EP 05786982 A 20050916; EP 2005054614 W 20050916; US 66733205 A 20050916