

Title (en)

DEVICE FOR HAND-DRIVEN OPERATION OF A GUIDED WHEEL

Title (de)

VORRICHTUNG ZUM HANDANTRIEB EINES GELENKTEN RADES

Title (fr)

SYSTEME DE COMMANDE MANUELLE D'UNE ROUE GUIDE

Publication

**EP 1817222 A2 20070815 (DE)**

Application

**EP 04789972 A 20041008**

Priority

- DE 2004002268 W 20041008
- DE 102004018662 A 20040413
- DE 102004031976 A 20040625

Abstract (en)

[origin: WO2005100142A2] The invention relates to a device for hand-driven operation of a guided wheel (R) which is arranged on a steering gear (1) and which can be pivoted about a steering axis (L) which is oriented in a perpendicular manner in relation to the axis of rotation (D) of the guided wheel, comprising a first handle (20), a first coupling device (21) arranged on the first handle (20), a second handle (22), a second coupling device (23) arranged on the second handle (22), a guiding device (2) which can be pivoted about the steering axis (L) and which mechanically cooperates with the steering device (1) for moveably mounting the handles (20,22) and with a power transmission train (3) which is coupled in a traction power transmitting manner to the second coupling device via coupling points in order to transmit a movement of the handles (20,22) to a drive device which cooperates with the hub (N) of the guided wheel (R) and which converts the movement of the handles (20,22) into a rotational movement of the guided wheel (R), wherein the guide device (2) includes restricted mechanical guidance of the handles (20,22) such that the handles (20,22) can be moved symmetrically in relation to a symmetrical plane of guidance wherein the steering axis (L) lies and which is oriented in a perpendicular manner in relation to the axis of rotation (D) of the guided wheel (R). According to the invention, the power transmission train (3) extends from the first coupling device (21) via deflecting elements (35,36,37,38), resulting in a modification of the direction of extension of the power transmission train (3), in a second power transmission section (31) to the second coupling device (23) such that the coupling devices (21,23) move the coupling pints of the power transmission train (3) on substantially linear drive paths.

IPC 8 full level

**B62M 1/00** (2006.01); **B62M 1/12** (2006.01); **B62M 1/14** (2006.01); **B62M 1/16** (2006.01)

CPC (source: EP US)

**B62M 1/12** (2013.01 - EP US); **B62M 1/14** (2013.01 - EP US); **B62M 1/16** (2013.01 - EP US); **Y10T 74/18568** (2015.01 - EP US);  
**Y10T 74/2078** (2015.01 - EP US)

Citation (search report)

See references of WO 2005100142A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

**DE 202004017142 U1 20050324**; DE 112004002825 A5 20070524; DE 112004002825 B4 20081030; EP 1817222 A2 20070815;  
US 2007227277 A1 20071004; US 7726676 B2 20100601; WO 2005100142 A2 20051027; WO 2005100142 A3 20070907

DOCDB simple family (application)

**DE 202004017142 U 20041008**; DE 112004002825 T 20041008; DE 2004002268 W 20041008; EP 04789972 A 20041008;  
US 57821906 A 20061011