

Title (en)
DIMENSIONALLY-OPTIMISED DEVICE FOR THE EXCHANGE OF HEAT AND METHOD FOR OPTIMISATION OF THE DIMENSIONS OF DEVICES FOR THE EXCHANGE OF HEAT

Title (de)
DIMENSIONSOPTIMIERTE VORRICHTUNG ZUM AUSTAUSCH VON WÄRME UND VERFAHREN ZUR OPTIMIERUNG DER DIMENSIONEN VON VORRICHTUNGEN ZUM AUSTAUSCH VON WÄRME

Title (fr)
DISPOSITIF D'ECHANGE DE CHALEUR A DIMENSIONS OPTIMISEES ET PROCEDE POUR OPTIMISER LES DIMENSIONS DE DISPOSITIFS D'ECHANGE DE CHALEUR

Publication
EP 1831632 A1 20070912 (DE)

Application
EP 05813950 A 20051117

Priority
• EP 2005012304 W 20051117
• DE 102004056557 A 20041123

Abstract (en)
[origin: WO2006056360A1] The invention relates to a device for the exchange of heat, in particular, for a motor vehicle, comprising a number of flow tubes for the transport of a fluid, whereby the device has a given depth (T) and, at least in sections, some flow tubes are arranged at a given separation from each other, whereby the depth and the given separation are in a ratio (V) to each other.

IPC 8 full level
F28D 1/053 (2006.01); **F25B 39/02** (2006.01)

CPC (source: EP US)
F25B 9/008 (2013.01 - EP US); **F25B 39/022** (2013.01 - EP US); **F28D 1/05383** (2013.01 - EP US); **F28F 1/126** (2013.01 - EP US); **F25B 2309/061** (2013.01 - EP US); **F25B 2500/01** (2013.01 - EP US); **F28D 2021/0085** (2013.01 - EP US)

Citation (search report)
See references of WO 2006056360A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
DE 102004056557 A1 20060524; BR PI0518471 A2 20081118; CN 101065635 A 20071031; CN 101065635 B 20101013; EP 1831632 A1 20070912; JP 2008520489 A 20080619; US 2008029242 A1 20080207; WO 2006056360 A1 20060601

DOCDB simple family (application)
DE 102004056557 A 20041123; BR PI0518471 A 20051117; CN 200580040052 A 20051117; EP 05813950 A 20051117; EP 2005012304 W 20051117; JP 2007541785 A 20051117; US 72001405 A 20051117