

Title (en)
ANCHORAGE FOR USE ON A ROOF

Title (de)
VERANKERUNG ZUR VERWENDUNG AUF EINEM DACH

Title (fr)
ANCORAGE DESTINE A ETRE UTILISE SUR UN TOIT

Publication
EP 1834056 B1 20161019 (EN)

Application
EP 06700786 A 20060104

Priority
• NL 2006050001 W 20060104
• NL 1027980 A 20050107

Abstract (en)
[origin: WO2006085765A2] Anchorage for a roof such as a flat or preferably sloping roof. The anchorage consists of an anchoring point such as an eye. According to the invention, said anchoring point can be moved back and forth in a direction essentially perpendicular to the roof from a position in which it is fitted essentially flush with the roof to a position in which it is projecting from the roof. For this purpose, there is a roof passage for the anchoring point, which roof passage part can be closed off with a cap that is preferably provided on the anchoring point. The anchoring point is accommodated so that it can be moved axially in a bush that is fixed by means of a plate construction on the outside of the roof. A corresponding plate construction is fixed on the inside of the roof, so that the roof becomes clamped between two plates. The axial movement is preferably achieved by screwing, so that it is possible to move the anchoring point outside by operation from the inside.

IPC 8 full level
E04G 21/32 (2006.01); **A62B 35/00** (2006.01); **E04D 1/30** (2006.01)

CPC (source: EP)
E04G 21/3261 (2013.01); **E04G 21/3276** (2013.01); **E04G 21/328** (2013.01); **A62B 35/0068** (2013.01)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 2006085765 A2 20060817; WO 2006085765 A3 20061019; DK 1834056 T3 20170123; EP 1834056 A2 20070919;
EP 1834056 B1 20161019; NL 1027980 C2 20060711; NO 20073514 L 20071002

DOCDB simple family (application)
NL 2006050001 W 20060104; DK 06700786 T 20060104; EP 06700786 A 20060104; NL 1027980 A 20050107; NO 20073514 A 20070706