

Title (en)
DEVICE AND METHOD FOR ALTERING AN ELECTROMAGNETIC RADIATION FIELD IN THE OPTICAL SPECTRAL RANGE IN PARTICULAR A LASER RADIATION FIELD

Title (de)
VORRICHTUNG UND VERFAHREN ZUR VERÄNDERUNG EINES ELEKTROMAGNETISCHEN STRahlungSFELDES DES OPTISCHEN SPEKTRALBEREICHES, INSBESONDERE EINES LASERSTRahlungSFELDES

Title (fr)
DISPOSITIF ET PROCEDE POUR MODIFIER UN CHAMP DE RAYONNEMENT ELECTROMAGNETIQUE DU DOMAINE SPECTRAL OPTIQUE, EN PARTICULIER UN CHAMP DE RAYONNEMENT LASER

Publication
EP 1834196 A1 20070919 (DE)

Application
EP 04804427 A 20041230

Priority
EP 2004014842 W 20041230

Abstract (en)
[origin: WO2006074681A1] The invention relates to a device for altering the intensity distribution of a laser radiation field, comprising two substrates (3, 4) with differing refractive indices ($n_{\text{SUB}2}$, $n_{\text{SUB}3}$) and with two opposed, mutually corresponding optical functional boundary surfaces (5, 6), which are at least partly curved. The laser radiation field for altering can pass serially through the optical functional boundary surfaces (5, 6), whereby the difference (Δn) in the refractive indices ($n_{\text{SUB}2}$, $n_{\text{SUB}3}$) of the first and second substrate (3, 4) is less than 0.1 and the cavity (9), between the first optical functional boundary surface (5) and the second optical functional boundary surface (6) is embodied such that the laser radiation, on propagation from the first substrate (3) into the second substrate (4), is essentially subjected to one refraction on the basis of the difference (Δn) in the refractive indices ($n_{\text{SUB}2}$, $n_{\text{SUB}3}$) of the first and second substrate (3, 4).

IPC 8 full level
G02B 3/00 (2006.01); **B23K 26/064** (2014.01)

CPC (source: EP US)
G02B 19/0014 (2013.01 - EP US); **G02B 19/0052** (2013.01 - EP US); **G02B 26/0875** (2013.01 - EP US); **G02B 27/0927** (2013.01 - EP US); **G02B 27/095** (2013.01 - EP US)

Citation (examination)

- DE 3033509 A1 19810423 - PERKIN ELMER CORP [US]
- GRECO V ET AL: "Optical contact and van der Waals interactions: the role of the surface topography in determining the bonding strength of thick glass plates; Optical contact and van der Waals interactions", JOURNAL OF OPTICS. A, PURE AND APPLIED OPTICS, INSTITUTE OF PHYSICS PUBLISHING, BRISTOL, GB, vol. 3, no. 1, 1 January 2001 (2001-01-01), pages 85 - 88, XP020080718, ISSN: 1464-4258, DOI: 10.1088/1464-4258/3/1/314
- RAYLEIGH F R S: "Glass surfaces in optical contact", PROCEEDINGS - ROYAL SOCIETY. MATHEMATICAL AND PHYSICAL SCIENCES, ROYAL SOCIETY, LONDON, GB, vol. 156, no. 888, 17 August 1936 (1936-08-17), pages 326 - 349, XP009159305, ISSN: 0962-8444, DOI: 10.1098/RSPA.1936.0151
- KACHKIN S S ET AL: "Effect of scale and time factors on the mechanical strength of an optical contact", SOVIET JOURNAL OF OPTICAL TECHNOLOGY, AMERICAN INSTITUTE OF PHYSICS, NEW YORK, NY, US, vol. 56, no. 2, 1 February 1989 (1989-02-01), pages 110 - 112, XP009159341, ISSN: 0038-5514
- See also references of WO 2006074681A1

Designated contracting state (EPC)
CH DE FR GB LI NL

DOCDB simple family (publication)
WO 2006074681 A1 20060720; CN 101107544 A 20080116; CN 101107544 B 20100505; EP 1834196 A1 20070919; JP 2008527402 A 20080724; JP 4527153 B2 20100818; US 2007297742 A1 20071227; US 7515347 B2 20090407

DOCDB simple family (application)
EP 2004014842 W 20041230; CN 200480044779 A 20041230; EP 04804427 A 20041230; JP 2007548698 A 20041230; US 82508207 A 20070702