

Title (en)
Milling cutter

Title (de)
Fräswerkzeug

Title (fr)
Fraise à fileter

Publication
EP 1834720 A1 20070919 (EN)

Application
EP 07104254 A 20070315

Priority
US 37886006 A 20060317

Abstract (en)

A milling cutter includes a milling-cutter body. The milling-cutter body includes a longitudinal axis, a proximal end portion, and a distal end portion (18). The distal end portion has a first cutting land (20), wherein the first cutting land, when viewed in a side elevational view, has an outline including a first substantially circular arc portion (22), a first substantially straight portion (24), a first transition zone (26) where the first substantially circular arc portion transitions to the first substantially straight portion, and a distal tip (28). The distal tip is located substantially on the longitudinal axis. The first substantially straight portion extends proximally from the distal tip to the first transition zone at an acute angle with respect to the longitudinal axis.

IPC 8 full level
B23C 5/10 (2006.01)

CPC (source: EP US)
B23C 5/10 (2013.01 - EP US); **B23C 2210/082** (2013.01 - EP US); **B23C 2210/084** (2013.01 - EP US); **B23C 2210/203** (2013.01 - EP US);
B23C 2210/54 (2013.01 - EP US); **Y10T 407/1948** (2015.01 - EP US)

Citation (search report)
• [X] US 2004151553 A1 20040805 - GEORGE STEPHEN M [US], et al
• [A] JP H09267211 A 19971014 - HITACHI TOOL

Cited by
CN103717336A; US9381582B2; WO2013004568A1

Designated contracting state (EPC)
DE FR GB

Designated extension state (EPC)
AL BA HR MK YU

DOCDB simple family (publication)
EP 1834720 A1 20070919; JP 2007245338 A 20070927; US 2007217874 A1 20070920

DOCDB simple family (application)
EP 07104254 A 20070315; JP 2007067818 A 20070316; US 37886006 A 20060317