

Title (en)

Multidaylight press for bonding flat elements, particularly for the hot or cold bonding of veneers, laminates or the like on sandwich, chipwood, honeycomb panels or the like and for producing plywoods, chipwood panels and the like

Title (de)

Mehretagenpresse zum Kleben von flachen Elementen, insbesondere zum Heiß- oder Kaltkleben von Furnieren, Schichtstoffen und dergleichen auf Schichtanordnungen, Faserholz, wabenförmige Platten und dergleichen und zur Herstellung von Sperrholzplatten, Faserholzplatten und dergleichen

Title (fr)

Presse à plateaux multiples pour lier des éléments plats, particulièrement pour la liaison à chaud et à froid des placages, laminés ou similaires sur des panneaux en sandwich, copeau ou en nid d'abeille et similaires, et pour produire des panneaux en contreplaqué, en copeau et similaires

Publication

**EP 1854622 A2 20071114 (EN)**

Application

**EP 07008939 A 20070503**

Priority

IT MI20060946 A 20060512

Abstract (en)

A multidaylight press comprises a framework (2) which supports: a fixed platen (3), a movable platen (4) which is parallel to the fixed platen (3) and can move on command toward or away from the fixed platen (3), and at least one intermediate platen (5), which is arranged between the fixed platen (3) and the movable platen (4) and is parallel thereto. The at least one intermediate platen (5) divides the space between the fixed platen (3) and the movable platen (4) into at least two daylight (6), which are adapted to accommodate the flat elements (10) to be pressed. The press is provided with first connection means (7), which are rigidly coupled to the framework (2), and second connection means (8), which are rigidly coupled to the movable platen (4). The intermediate platen (5) is provided with locking means (9) which can engage on command the first connection means (7) in order to rigidly couple the intermediate platen (5) to the framework (2) or the second connection means (8) in order to rigidly couple the intermediate platen (5) to the movable platen (4), or can disengage from both the first connection means (7) and the second connection means (8). Presser means (11) are further provided to press, with a preset pressure, the movable platen (4) toward the fixed platen (3) for pressing the flat elements (10) inserted in the daylight (6).

IPC 8 full level

**B30B 7/02** (2006.01)

CPC (source: EP)

**B30B 7/02** (2013.01); **B30B 7/023** (2013.01)

Citation (applicant)

GB 995590 A 19650616 - BUZULUK KOMAROV

Cited by

CN105291466A; EP1970192A3; CN113386220A; CN109624370A; US9085117B1

Designated contracting state (EPC)

DE ES IT

Designated extension state (EPC)

AL BA HR MK YU

DOCDB simple family (publication)

**EP 1854622 A2 20071114**; **EP 1854622 A3 20081105**; **EP 1854622 B1 20110302**; DE 602007012788 D1 20110414; ES 2361340 T3 20110616; IT MI20060946 A1 20071113

DOCDB simple family (application)

**EP 07008939 A 20070503**; DE 602007012788 T 20070503; ES 07008939 T 20070503; IT MI20060946 A 20060512