

Title (en)  
RELEASABLE COUPLING

Title (de)  
LÖSBARE VERBINDUNG

Title (fr)  
ACCOUPLEMENT DÉTACHABLE

Publication  
**EP 1856358 B1 20090708 (EN)**

Application  
**EP 05706797 A 20050228**

Priority  
DK 2005000135 W 20050228

Abstract (en)  
[origin: WO2006089545A1] Releasable coupling (1) comprising a male part (2) and a female part (3), said male part (2) having a head portion (4), and said female part (3) having a base part (30) with a recess (6) for said head portion (4), said female part further having a yielding closure member (7) biased in a direction to at least partially cover the recess (6). To provide a coupling which is less demanding with regard to precise mutual positioning of the coupling parts at installation thereof, the closure member (7) is adapted for cooperation with said male part (2) in a first mutual angular position of the male and female parts (2, 3), in which the male and female parts (2, 3) are in non-positive engagement to allow release of the head portion (4) of the male part (2) from the recess (6), and a second mutual angular position in which the male and female parts (2, 3) are held in positive engagement by the closure member (7) to hinder release of the head portion (4) of the male part (2) from the recess (6).

IPC 8 full level  
**E05F 11/06** (2006.01); **E05F 15/12** (2006.01)

CPC (source: EP)  
**E05F 11/06** (2013.01); **E05F 15/619** (2015.01); **E05D 7/1066** (2013.01); **E05Y 2201/656** (2013.01); **E05Y 2201/724** (2013.01); **E05Y 2900/152** (2013.01)

Cited by  
EP2957700A1; EP3770355A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**WO 2006089545 A1 20060831**; AT E435958 T1 20090715; DE 602005015364 D1 20090820; EP 1856358 A1 20071121; EP 1856358 B1 20090708; PL 1856358 T3 20091231

DOCDB simple family (application)  
**DK 2005000135 W 20050228**; AT 05706797 T 20050228; DE 602005015364 T 20050228; EP 05706797 A 20050228; PL 05706797 T 20050228