

Title (en)

Light reflector with defined acutance of the light distribution generated by the same

Title (de)

Lichtreflektor mit definierter Konturenschärfe der von diesem erzeugten Lichtverteilung

Title (fr)

Réflecteur de lumière doté de contours nets définis de la répartition de la lumière produite par celui-ci

Publication

EP 1857735 B1 20120606 (DE)

Application

EP 07009598 A 20070514

Priority

DE 102006023120 A 20060516

Abstract (en)

[origin: EP1857735A1] The reflector (1) has a reflection surface comprising a facet in sections, and a retainer (5) for an illuminant e.g. LED. The facet is provided with a cylindrical form in an illuminant close area (2), and is provided with a spherical form in an illuminant distant area (3). A periphery runs between the illuminant close and distant areas along an intersection line of a plane that runs perpendicular to a symmetric axis. The illuminant close area takes up between 20 to 35 percentages of the refraction surface.

IPC 8 full level

F21V 7/09 (2006.01); **F21V 7/22** (2006.01); **F21V 14/02** (2006.01)

CPC (source: EP US)

F21V 7/09 (2013.01 - EP US); **F21V 19/0005** (2013.01 - EP US)

Citation (examination)

- US 4484254 A 19841120 - PUCKETT CLARENCE D [US], et al
- GB 2004047 A 19790321 - SASSMANNSHAUSEN KNUT
- GB 2065287 A 19810624 - TOSHIBA ELECTRIC EQUIP

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1857735 A1 20071121; EP 1857735 B1 20120606; CN 101078495 A 20071128; CN 101078495 B 20110406;
DE 102006023120 A1 20071122; DE 102006023120 B4 20101014; JP 2007311353 A 20071129; US 2007268706 A1 20071122;
US 7547120 B2 20090616

DOCDB simple family (application)

EP 07009598 A 20070514; CN 200710128265 A 20070515; DE 102006023120 A 20060516; JP 2007130728 A 20070516;
US 74882307 A 20070515