

Title (en)

Operational-error preventing device for loom

Title (de)

Vorrichtung zum Vermeiden von Operativfehlern für eine Webmaschine

Title (fr)

Dispositif de prévention d'erreurs d'opération pour métier à tisser

Publication

EP 1862573 B1 20090819 (EN)

Application

EP 07008338 A 20070424

Priority

JP 2006155376 A 20060602

Abstract (en)

[origin: EP1862573A1] In an operational-error preventing device for a loom (1), a reverse-rotation prohibition angle is preliminarily set within a main-shaft-angle range in which a shedding device (50) is driven on the basis of an inverted shedding pattern. When a main-shaft angle reaches the reverse-rotation prohibition angle due to an automatic reverse rotation of a loom main shaft (24) to a set angle executed after the loom main shaft (24) has been stopped in response to an occurrence of a cause of stoppage or due to a reverse rotation executed in response to input of a reverse-rotation button signal (S3), the reverse rotation of the loom main shaft (24) is prohibited even if the reverse-rotation button signal (S3) is received.

IPC 8 full level

D03D 51/00 (2006.01)

CPC (source: EP)

D03C 19/005 (2013.01); **D03D 51/002** (2013.01)

Designated contracting state (EPC)

BE CH DE IT LI

DOCDB simple family (publication)

EP 1862573 A1 20071205; **EP 1862573 B1 20090819**; CN 101082148 A 20071205; CN 101082148 B 20110126; DE 602007002007 D1 20091001; JP 2007321313 A 20071213; JP 5084179 B2 20121128

DOCDB simple family (application)

EP 07008338 A 20070424; CN 200710103498 A 20070518; DE 602007002007 T 20070424; JP 2006155376 A 20060602