

Title (en)  
DEVICE FOR BREAKING BREAKABLE RODS AND ASSOCIATED METHOD

Title (de)  
VORRICHTUNG ZUM BRECHEN BRECHBARER STÄBE UND ENTSPRECHENDES VERFAHREN

Title (fr)  
DISPOSITIF DE CASSAGE DE BIELLES SECABLES ET PROCEDE ASSOCIE

Publication  
**EP 1866120 B1 20120502 (FR)**

Application  
**EP 06726288 A 20060330**

Priority  
• FR 2006050274 W 20060330  
• FR 0503094 A 20050330

Abstract (en)  
[origin: WO2006103373A1] The invention relates to a rod-breaking device (1) comprising: a tenon (15), a fixed longitudinal block (11), a mobile longitudinal block (12) and two lateral blocks (13, 14), each block comprising a cylindrical section of the same radius. According to the invention, the aforementioned blocks are mounted such that they can occupy an extended position and a retracted position in which the axes of the cylindrical sections are aligned and define the axis of the device. A mortise housing a tenon (15) extends through said assembly along the axis of the device. The tenon (15) is equipped with at least three sides (26, 28, 29) that are inclined in relation to the axis of the device, namely: a longitudinal side (26) which co-operates with an inclined side (33) of the mobile longitudinal block (12) and two lateral sides (28, 29) which each co-operate with one of the inclined sides (35, 36) of each of the lateral blocks (13, 14), the axis of the longitudinal side (26) forming an angle with each of the axes of the two lateral sides (28, 29).

IPC 8 full level  
**B23D 31/00** (2006.01)

CPC (source: EP)  
**B23D 31/003** (2013.01); **F16C 9/045** (2013.01)

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**WO 2006103373 A1 20061005**; AT E555864 T1 20120515; EP 1866120 A1 20071219; EP 1866120 B1 20120502; FR 2883781 A1 20061006; FR 2883781 B1 20080808

DOCDB simple family (application)  
**FR 2006050274 W 20060330**; AT 06726288 T 20060330; EP 06726288 A 20060330; FR 0503094 A 20050330