

Title (en)

OVER-MOLDED BOLT FOR A STEERING WHEEL LOCK AND METHOD FOR THE PRODUCTION THEREOF

Title (de)

UMSPRITZTER RIEGEL FÜR LENKSÄULENSCHLOSS UND VERFAHREN ZUR HERSTELLUNG DERSELBEN

Title (fr)

PENE SURMOULE POUR ANTIVOL DE DIRECTION ET SON PROCEDE DE FABRICATION

Publication

EP 1882071 A1 20080130 (FR)

Application

EP 06754881 A 20060427

Priority

- EP 2006061870 W 20060427
- FR 0504852 A 20050513

Abstract (en)

[origin: FR2885632A1] The method involves forming a rough-cast core (1) in steel, by a casting gravity mold. The core is partly or entirely molded using a resin layer (2). The resin layer is supported by the core when a force is applied on a bolt (P) which has notches (5, 6) and an orifice (3). The core has shapes greater than one-tenth of a millimeter.

IPC 8 full level

E05B 15/16 (2006.01); **B29C 43/18** (2006.01); **B60R 25/021** (2013.01); **E05B 15/10** (2006.01)

CPC (source: EP)

B60R 25/0211 (2013.01); **E05B 15/10** (2013.01); **B29C 45/14** (2013.01); **B29K 2705/00** (2013.01); **E05B 2015/165** (2013.01)

Citation (search report)

See references of WO 2006122869A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

FR 2885632 A1 20061117; **FR 2885632 B1 20070622**; EP 1882071 A1 20080130; WO 2006122869 A1 20061123

DOCDB simple family (application)

FR 0504852 A 20050513; EP 06754881 A 20060427; EP 2006061870 W 20060427