

Title (en)
LOCK WITH ROTOR FIXING ELEMENT

Title (de)
SCHLOSS MIT DREHZYLINDERFESTLEGUNGSELEMENT

Title (fr)
VERROU À ÉLÉMENT DE FIXATION DU ROTOR

Publication
EP 1882072 A1 20080130 (FR)

Application
EP 06754784 A 20060421

Priority
• EP 2006061730 W 20060421
• FR 0504654 A 20050510

Abstract (en)
[origin: FR2885631A1] The lock has rotor and stator assemblies, where the rotor assembly includes a front axial end (11) and a retaining unit (13). The axial end cooperates with a sub assembly universal joint (12) to lock and unlock an opening of a vehicle when a key is introduced in the lock. The retaining unit is fixed by a clipping unit (16) on the stator assembly after the rotor and the stator assemblies are mounted and fixed between them. The retaining unit comprises a set of lugs (15) and a circular part that is supported against the rotor assembly, where the retaining unit is a metal e.g. steel.

IPC 8 full level
E05B 9/08 (2006.01); **E05B 17/20** (2006.01)

CPC (source: EP KR US)
E05B 9/086 (2013.01 - EP US); **E05B 17/20** (2013.01 - KR); **E05B 17/2084** (2013.01 - EP US); **E05B 2017/2096** (2013.01 - EP US); **Y10T 70/5155** (2015.04 - EP US)

Citation (search report)
See references of WO 2006122863A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
FR 2885631 A1 20061117; FR 2885631 B1 20080905; BR PI0608790 A2 20100126; CN 101218404 A 20080709; EP 1882072 A1 20080130; EP 1882072 B1 20160511; JP 2008540877 A 20081120; KR 20080014839 A 20080214; MX 2007014090 A 20080207; US 2008196455 A1 20080821; WO 2006122863 A1 20061123

DOCDB simple family (application)
FR 0504654 A 20050510; BR PI0608790 A 20060421; CN 200680025201 A 20060421; EP 06754784 A 20060421; EP 2006061730 W 20060421; JP 2008510530 A 20060421; KR 20077028718 A 20071207; MX 2007014090 A 20060421; US 91389706 A 20060421