

Title (en)  
High temperature forging die

Title (de)  
Gesenk zum Hochtemperaturschmieden

Title (fr)  
Matrice de forgeage à haute température

Publication  
**EP 1886743 B1 20110615 (DE)**

Application  
**EP 07014357 A 20070721**

Priority  
DE 102006037883 A 20060811

Abstract (en)  
[origin: EP1886743A1] The die for high temperature mild intermetallic component for the production of aircraft engine or stationary gas turbines or its shovel, comprises upper and lower particle or fiber reinforced die parts (4), which are connected with a reinforcement ring (7) over a stop element. Each die part is assigned as the reinforcement ring surrounding with fixture by ambient temperature. The die parts are placed on the ring due to its thermal expansion during heating. A compressive stress is exerted on the die part by the reinforcement ring. The die part is ceramic or graphite. The die for high temperature mild intermetallic component for the production of aircraft engine or stationary gas turbines or its shovel, comprises upper and lower particle or fiber reinforced die parts (4), which are connected with a reinforcement ring (7) over a stop element. Each die part is assigned as the reinforcement ring surrounding with fixture by ambient temperature. The die parts are placed on the ring due to its thermal expansion during heating. A compressive stress is exerted on the die part by the reinforcement ring. The die part is ceramic or graphite and the reinforcement ring consists of a fiber reinforced composite with wrapped carbon fiber. The fixture is designed by ambient temperature under circumstances of the expansion behavior of the die part and the ring in such a way that the constructed compressive stress is implemented by a predetermined value of a mild temperature. The reinforcement ring has an internal bearer ring (9) on which the heated die part adjoins. The bearer ring has projections (11) serving the support of the inserted die part and is sectionally closed at a side. The projection is intended at rotating edge side around 180[deg]. The die parts are intended at forcible guidance cooperated with compatible place of the die part. The guidance has fiber reinforced bolts or plug that is interfered into the bolt- or plug reception at the opposite die part. The bolt or plug exists out of ceramic or graphite. The die parts have die part elements (5, 6) and gravures. The stop element is a peg that is received in corresponding sockets at the reinforced ring and at the die part or the die part element.

IPC 8 full level  
**B21J 13/02** (2006.01); **B21J 5/02** (2006.01)

CPC (source: EP US)  
**B21J 5/02** (2013.01 - EP US); **B21J 9/08** (2013.01 - EP US); **B21J 13/02** (2013.01 - EP US)

Cited by  
CN105033133A; WO2016091453A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 1886743 A1 20080213**; **EP 1886743 B1 20110615**; AT E512738 T1 20110715; DE 102006037883 A1 20080214; DE 102006037883 B4 20080731; ES 2368006 T3 20111111; JP 2008044012 A 20080228; JP 4916976 B2 20120418; US 2008072651 A1 20080327; US 7836744 B2 20101123

DOCDB simple family (application)  
**EP 07014357 A 20070721**; AT 07014357 T 20070721; DE 102006037883 A 20060811; ES 07014357 T 20070721; JP 2007206386 A 20070808; US 88106707 A 20070725