

Title (en)

NOZZLE BEAM WITH MEANS FOR SETTING WORKING WIDTH AND METHOD FOR SETTING THE WORKING WIDTH OF A NOZZLE STRIP

Title (de)

DÜSENBAKELN MIT MITTELN ZUR EINSTELLUNG DER ARBEITSBREITE SOWIE VERFAHREN ZUR EINSTELLUNG DER ARBEITSBREITE EINES DÜSENSTREIFENS

Title (fr)

BARRE A BUSES COMPORTANT DES ELEMENTS DE REGLAGE DE LA LARGEUR DE TRAVAIL ET PROCEDE DE REGLAGE DE LA LARGEUR DE TRAVAIL D'UNE BANDE A BUSES

Publication

EP 1891259 A1 20080227 (DE)

Application

EP 06706252 A 20060117

Priority

- EP 2006000345 W 20060117
- DE 102005005463 A 20050204

Abstract (en)

[origin: US7441315B2] The nozzle beam is arranged on a device for generation of liquid streams for the treatment of fibres of a material web running along the nozzle beam. The nozzle beam comprises an upper piece (4), running across the working width of the web and a lower piece (5), which runs out into a liquid outlet slot (10). According to the invention, a nozzle strip (14) is arranged below the liquid outlet slot (10) and an easily detachable so-called masking strip (18) is mounted directly above the above in a liquid-tight manner, when viewed in the flow direction of the water jet. A part of the nozzle outlet opening on the nozzle strip is covered by the masking strip (18) and a part is left free, whereby liquid jets emerge from the part left free and form a continuous liquid curtain. According to the invention, a nozzle strip (14) with a maximum stream width is fitted to the nozzle beam. When a reduced stream width is required, a corresponding masking strip (18) is fitted which covers the non-required nozzle drillings in the outer regions of the nozzle strip (14). A simple and economical adjustment of the working width is thus possible, only that energy required for the process is used and the components guiding the material web are protected. Furthermore, the splash water flow into the plant is avoided.

IPC 8 full level

B05B 1/28 (2006.01); **D04H 18/04** (2012.01)

CPC (source: EP US)

B05B 1/1627 (2013.01 - EP US); **B05B 1/20** (2013.01 - EP US); **D04H 18/04** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

US 2008092935 A1 20080424; US 7441315 B2 20081028; AT E434675 T1 20090715; DE 102005005463 A1 20060810;
DE 502006004071 D1 20090806; EP 1891259 A1 20080227; EP 1891259 B1 20090624; ES 2325419 T3 20090903; JP 2008528282 A 20080731;
JP 4874998 B2 20120215; PL 1891259 T3 20091231; WO 2006081938 A1 20060810

DOCDB simple family (application)

US 7957006 A 20060117; AT 06706252 T 20060117; DE 102005005463 A 20050204; DE 502006004071 T 20060117;
EP 06706252 A 20060117; EP 2006000345 W 20060117; ES 06706252 T 20060117; JP 2007553492 A 20060117; PL 06706252 T 20060117