

Title (en)

SCREW FOR USE IN CONCRETE

Title (de)

SCHRAUBE ZUR VERWENDUNG IN BETON

Title (fr)

VIS À UTILISER DANS LE BÉTON

Publication

EP 1891340 A1 20080227 (EN)

Application

EP 06741570 A 20060529

Priority

- CA 2006000861 W 20060529
- CA 2510200 A 20050616
- US 16142505 A 20050802

Abstract (en)

[origin: WO2006133542A1] The concrete screw of the invention reduces the driving torque required, reduces shear failure, and provides increased pull-out resistance. The screw has Hi-Low threads, the major thread being of greater diameter than the minor thread, the threads having a pitch displacement at least equal to the diameter of the screw shank. Helical grooves of opposite rotational hand from the threads extend the length of the threaded portion of the screw, and have a pitch displacement at least two times the diameter of the screw shank. In a limited portion adjacent the tip of the screw, and extending generally no more than 1/3 of the length of the threads, are intermediate helical counter-rotation grooves. The intermediate grooves may be adjacent the principal grooves to produce a W-shaped notch in the threads. Preferably, the W-shaped notch is asymmetrical in the direction of rotation of the grooves.

IPC 8 full level

F16B 25/02 (2006.01); **F16B 35/04** (2006.01); **F16B 39/30** (2006.01)

CPC (source: EP)

F16B 25/0026 (2013.01); **F16B 25/0052** (2013.01); **F16B 25/0068** (2013.01); **F16B 25/0073** (2013.01); **F16B 25/0078** (2013.01);
F16B 25/10 (2013.01); **F16B 35/048** (2013.01); **F16B 39/30** (2013.01)

Citation (search report)

See references of WO 2006133542A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

WO 2006133542 A1 20061221; WO 2006133542 A8 20080117; EP 1891340 A1 20080227

DOCDB simple family (application)

CA 2006000861 W 20060529; EP 06741570 A 20060529