Title (en)

System for widening a fibre web, method for controlling the transfer of a web tail and machine for producing a sheet of fibrous material

Title (de)

System zum Breitfahren einer Faserstoffbahn, Verfahren zur Steuerung der Randstreifenüberführung und Maschine zur Herstellung einer Faserstoffbahn

Title (fr)

Système pour élargir une bande fibreuse, procédé de controller le transfert de la bande directrice et machine pour la fabrication d'une bande fibreuse

Publication

EP 1903142 B1 20110427 (DE)

Application

EP 07111929 A 20070706

Priority

DE 102006044930 A 20060922

Abstract (en)

[origin: EP1903142A1] One or more stabilization units (15), stabilize the web remaining (4.2), between the initial position (A) and the end position (E) of the cutter unit, seen across the machine direction. Cutter and stabilizer (15) are arranged separately in succession along the machine. The operating width of the stabilizer extends across the entire width of the remaining web, corresponding with the operational width of the cutter between start and end positions. It alternatively extends over the entire web width. The stabilizer operational width is adjustable. At least one cutter is included, its initial position (A) corresponding with the desired width of the transfer- or edge strip (4.1) at the side of the web. A dual cutting arrangement is described. The stabilizer has adjacent, individually-controlled components, disposed across the machine. The stabilizer includes film panels adjustable through an angle in relation to the direction of travel of the web remaining. They are swung by an adjuster unit. A suction unit and suction zone are associated with each film panel. In variant designs, the stabilizer on flow. The flow is provided by a fluid jet, the fluid being e.g. water, gas, gas fluid mixture, steam or air. The cutter is a fluid jet. It is alternatively a blade. A unit (25) supports strip transfer. Further mechanical details are provided. The equipment forms part of a papermaking machine with a wet section, drying section and system for controlling web width as described. The cutter is in the wet section or at the start of the drying section, and the stabilizer is in the drying section. An independent claim IS INCLUDED FOR the corresponding method of manufacture.

IPC 8 full level

CPC (source: EP)

D21F 7/04 (2006.01); D21G 9/00 (2006.01)

D21F 7/04 (2013.01); D21G 9/0063 (2013.01)

Cited by

WO2021121992A1; EP2058433A3; DE102019134691A1; EP4077804B1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1903142 A1 20080326; EP 1903142 B1 20110427; AT E507347 T1 20110515; CN 101148838 A 20080326; CN 101148838 B 20121121; DE 102006044930 A1 20080403; DE 502007007045 D1 20110609

DOCDB simple family (application)

EP 07111929 A 20070706; AT 07111929 T 20070706; CN 200710152895 A 20070921; DE 102006044930 A 20060922; DE 502007007045 T 20070706