

Title (en)
OPTIMIZED SUPPORT ELEMENT

Title (de)
OPTIMIERTES STÜTZELEMENT

Title (fr)
APPUI DE SOUTIEN OPTIMISE

Publication
EP 1910104 A1 20080416 (FR)

Application
EP 06764206 A 20060719

Priority
• EP 2006064405 W 20060719
• FR 0507791 A 20050719

Abstract (en)
[origin: WO2007010003A1] The invention relates to a support element to be mounted on a rim inside a tire on a vehicle for supporting the tread of this tire in the event of a loss in filling pressure. The support element comprises, a base, a top and an annular body in which each support wall of the annular body has a slanted parallelepiped shape with two circumferentially oriented outer faces placed on both sides of the support element and two faces that are slanted in relation to the circumferential direction of an angle α , two adjacent support walls forming a V-shaped pattern, and at the base of V, two adjacent support walls are separated by a narrow lateral slit radially extending over the entire annular body.

IPC 8 full level
B60C 17/06 (2006.01); **B60C 17/04** (2006.01)

CPC (source: EP US)
B60C 17/06 (2013.01 - EP US); **B60C 17/061** (2013.01 - EP)

Citation (search report)
See references of WO 2007010003A1

Cited by
CN107580558A

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
FR 2888778 A1 20070126; CN 101223044 A 20080716; EP 1910104 A1 20080416; JP 2009501668 A 20090122; US 2008295942 A1 20081204; WO 2007010003 A1 20070125

DOCDB simple family (application)
FR 0507791 A 20050719; CN 200680026118 A 20060719; EP 06764206 A 20060719; EP 2006064405 W 20060719; JP 2008521966 A 20060719; US 99624206 A 20060719