

Title (en)
Desuperheater apparatus for steam lines

Title (de)
Dampfkühlungsvorrichtung für Dampfleitungen

Title (fr)
Appareil désurchauffeur pour conduites de vapeur

Publication
EP 1918532 A1 20080507 (EN)

Application
EP 06425745 A 20061030

Priority
EP 06425745 A 20061030

Abstract (en)
A desuperheater apparatus (1) for steam lines, which comprises a plurality of chambers (2, 3, 4) including a final chamber (4) whose upstream end is closed by a steam diffuser (11) having a plurality of holes (12) for the passage of steam. Spray nozzles (9) are associated to the final chamber (4) for generating respective spray cones therein. Advantageously, the steam diffuser (11) has a conical shape so that, at each spray nozzle (9), the perforated portions of the steam diffuser (11) are inclined in such a manner as to be substantially parallel to the lateral surface of the spray cones (C) generated by their corresponding spray nozzles.

IPC 8 full level
F01K 3/00 (2006.01); **F22G 5/12** (2006.01); **F22G 5/14** (2006.01)

CPC (source: EP)
F01K 3/002 (2013.01); **F22G 5/126** (2013.01)

Citation (search report)

- [A] DE 3720918 C1 19881124 - WELLAND & TUXHORN
- [A] EP 0025341 A1 19810318 - SULZER AG [CH]
- [A] WO 9404255 A1 19940303 - BTG KAELE INVENTING AB [SE], et al
- [A] EP 1326048 A1 20030709 - DRESSER INC [US]
- [A] KAUER G: "HEISSDAMPFKUEHLUNG DURCH WASSEREINSPRITZUNG IN WAERMETECHNISCHEN ANLAGEN", VGB KRAFTWERKSTECHNIK, VGB KRAFTWERKSTECHNIK GMBH. ESSEN, DE, vol. 78, no. 9, 1998, pages 50 - 59, XP000776949, ISSN: 0372-5715

Cited by
US9885473B2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA HR MK RS

DOCDB simple family (publication)
EP 1918532 A1 20080507; EP 1918532 B1 20160420; ES 2574011 T3 20160614

DOCDB simple family (application)
EP 06425745 A 20061030; ES 06425745 T 20061030