

Title (en)
Stop device for the opening and closing of a blind

Title (de)
Anschlageinrichtung für die Öffnungs- und Schließbewegung einer Verschattungsanlage

Title (fr)
Dispositif de butée pour le mouvement d'ouverture et de fermeture d'une installation d'obscurcissement

Publication
EP 1921246 B1 20111221 (DE)

Application
EP 07120227 A 20071108

Priority
DE 102006052969 A 20061108

Abstract (en)
[origin: EP1921246A2] The device has a stopper pin, a spring unit (20) and a stopper socket (15) that is movable between the stopper pin and the spring unit. The stopper socket is coupled with an opening and closing movement of a shading system in a kinematic manner. The pin and/or the spring unit are fixable at a desired stopper position by a clamping unit (30). The clamping unit is arranged outside a winding shaft for hangings, and is arranged in an axial direction of the winding shaft. The pin and the spring unit are adjustable.

IPC 8 full level
E06B 9/40 (2006.01); **E06B 9/42** (2006.01); **E06B 9/50** (2006.01); **E06B 9/56** (2006.01); **E06B 9/68** (2006.01); **E06B 9/72** (2006.01); **E06B 9/90** (2006.01); **E06B 9/88** (2006.01)

CPC (source: EP)
E06B 9/72 (2013.01); **E06B 9/88** (2013.01); **E06B 2009/6881** (2013.01)

Cited by
US10501988B2; DE102010010648A1; EP1983145A3; CN104343378A; US9714539B2; WO2012093092A1; US11970906B2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1921246 A2 20080514; **EP 1921246 A3 20101027**; **EP 1921246 B1 20111221**; AT E538282 T1 20120115; DE 102006052969 A1 20080515; DE 102006052969 B4 20080717

DOCDB simple family (application)
EP 07120227 A 20071108; AT 07120227 T 20071108; DE 102006052969 A 20061108